## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

<u>Tensility International Corporation</u> 10-00430

For any questions, you can email us directly: sales@integrated-circuit.com



### Distributor of Tensility International Corporation: Excellent Integrated System Limited

Datasheet of 10-00430 - CBL ASSY MINI DIN FEMALE 6' 7POS

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

part number: 10-00430 description:

Cable, 1830 mm, 7P mini-DIN female

rev: Α 50-00167, to stripped tinned, 20 AWG, page: 1 of 2 UL2464 30-00027, shielded

date: March 9, 2011


#### **Specifications:**

7P mini DIN female, molding style, brass, nickel plating, P/N 50-00167
inner: PE; outer: 60P, PVC, black
7C, 20 AWG, UL2464, 300 V, 80 C, 7.5 mm, shielded, VW-1, PVC, 60P, P/N 30-00027
Ø7.5 mm
black
1830 ± 50 mm
black
Ø8.0, 105°C, 10 ± 2 mm, black
Ø1.0, 105°C, 30 ± 5 mm, black
2 A @ 12 Vdc

#### Notes:

Function test: no open, no reversed polarity, no short circuit, no INT RoHS compliant

**Mechanical drawing:** 



tolerance X: ±0.5 mm .X: ±0.3 mm .XX: ±0.05 mm applicable unless otherwise indicated in specification or on drawings Tensility International Corporation reserves the right to substitute parts which are functionally equivalent to the ones specified.

**Initial Date** 



## Distributor of Tensility International Corporation: Excellent Integrated System Limited

Datasheet of 10-00430 - CBL ASSY MINI DIN FEMALE 6' 7POS

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

TENSILITY

part number: 10-00430 description: Cable, 183

Cable, 1830 mm, 7P mini-DIN female 50-00167, to stripped tinned, 20 AWG,

UL2464 30-00027, shielded

date: March 9, 2011

rev: A page: 2 of 2

Revision notes:				
Rev	Date	Description		
Α	March 9, 2011	initial release		

# A March 9, 2011 Initial release

#### **Specification Approval**

Spec sign-off verifies that you have reviewed the entire specification, tested a sample of the product, and confirm that it meets your requirements. This specification reflects the part as it will be ordered. Orders will not be processed until the specification pages have been initialed and the approval page has been signed. This specification is confidential and is not to be transmitted without prior approval from Tensility.

Signature	Title ————
Name	Date
Company	Branch