

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1780477](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

PTPM 0,2/ 2-P-2,5

Order No.: 1780477



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1780477>

Plug component, Nominal current: 2 A, Rated voltage (III/2): 160 V, Number of positions: 2, Pitch: 2.5 mm, Color: black, Metal surface: Sn

Commercial data

GTIN (EAN)	 4 046356 536127
sales group	E410
Pack	250 pcs.
Customs tariff	85366990
Catalog page information	Page 183 (NTK-2010)

Product notes

WEEE/RoHS-compliant since:
10/06/2009



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions / positions

Pitch	2.5 mm
Dimension a	2.5 mm
Number of positions	2

PTPM 0,2/ 2-P-2,5 Order No.: 1780477

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1780477>
Technical data

Range of articles	PTPM 0,2/...-P
Insulating material group	III
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/2)	160 V
Rated voltage (II/2)	160 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	2 A
Nominal voltage U_N	40 V
Nominal cross section	0.14 mm ²
Maximum load current	2 A
Insulating material	PA/PC
Inflammability class acc. to UL 94	V0/V2
Nominal voltage, UL/CUL Use Group B	50 V
Nominal current, UL/CUL Use Group B	2 A
Nominal voltage, UL/CUL Use Group D	50 V
Nominal current, UL/CUL Use Group D	2 A

Connection data

Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	0.14 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	26
Maximum AWG according to UL/CUL	26

Certificates / Approvals


Certification


CUL, UL

PTPM 0,2/ 2-P-2,5 Order No.: 1780477

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1780477>


Diagrams/Drawings

Diagram



Derating curve for: PTPM 0.2/...-P-2.5 with PTSM 0.5/...-HH-2.5-THR R..

Dimensioned drawing



PTPM 0,2/ 2-P-2,5 Order No.: 1780477

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1780477>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;