

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:



[Molex Connector Corporation](#)
[0002061132](#)

For any questions, you can email us directly:


sales@integrated-circuit.com

PART NO. ENG. NO.

02-06-1131	1855-(P901)	
02-06-1132	1855-(P901)L	
02-06-5137	1855-(P591)	OBSOLETE
02-06-5136	1855-(P591)L	OBSOLETE
02-06-5138	1855-(P561)	
02-06-5139	1855-(P561)L	
02-06-5130	1855-(P550)	
02-06-5135	1855-(P550)L	
02-06-5147	1855-(P228)	
02-06-5148	1855-(P228)L	
02-06-1141	1855-(1P901)	
NOT TOOLED	1855-(1P901)L	
02-06-1143	1855-(P901)1	



SECT. "B-B"
SCALE:10X



SECT. "C-C"
SCALE:10X

LEGEND

1855-*(*)**)*
 BLANK-WITH LOCKING TABS
 1-WITHOUT LOCKING TABS
 P=PREPLATE
 BLANK=POSTPLATE
 FORM
 BLANK=CHAIN
 1=CHAIN WITH INTERLEAF
 PAPER ON REEL.
 L=LOOSE
 FINISH CODE

NOTES:

- MATERIAL: BRASS
- FINISHES:
 901 HOT TIN DIP (.0005)/.000020 MIN.
 * 228 SELECT GOLD PLATE (.00075)/.000030 MIN. IN CONTACT AREA, SELECT TIN (.00250)/.000100 MIN. IN CRIMP AREA OVER (.00125)/.000050 MIN. NICKEL OVERALL, WITH (.000010)/.000025 MAX. SELECT GOLD FLASH IN AREA INDICATED.
 561 SELECT GOLD PLATE (.00076)/.000030 MIN. IN CONTACT AREA, (.00127)/.000050 MIN. NICKEL OVERALL.
 591 SELECT GOLD PLATE (.00127)/.000050 MIN. IN CONTACT AREA, OVER (.00127)/.000050 MIN. NICKEL OVERALL WITH (.00025)/.000010 MAX. GOLD FLASH OVERALL.
 550 SELECT GOLD PLATE (.00038)/.000015 MIN. IN CONTACT AREA, OVER (.00076)/.000030 MIN. NICKLE OVERALL WITH (.00025)/.000010 MAX. GOLD FLASH OVERALL.
 * THE PRIMARY SHIPPING CARTON WILL BE LABELED, "COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC THIS LABEL MAY CONTAIN PRODUCT WITH TIN-LEAD.
- PRODUCT SPECIFICATION: PS-02-0-6
- PACKAGE INFORMATION: NOT AVAILABLE
- TERMINAL FOR USE WITH (1.57)/.062 DIA. SERIES HOUSINGS AND WILL ACCEPT 24 THRU 30 AWG WIRE WITH (1.02/2.29)/.040/.090 INSULATION DIAMETER.

(.25) MAX.
.010
CARRIER CUTOFF

(16.8) .66

(.25) MAX.
.010
CARRIER CUTOFF

(2.03) .080

(1.93) .076

SECT. "A-A"

AP	REVISE SHIP PLATE REDRAWN TO NEW UCP2004-2097 5/07/04 RHOLTS
AN	OBSOLETE P/N UCR2002-0270 CHERO 01/19/28
AM1	OBSOLETE P/N UCR2002-0270 CHERO 01/19/28
AM	REV. AND REDRAWN PER ECR 10372 SEP 6-17-87 RW

REV. MATL. SPEC. STAT. TO NEW	EC NO. UCP2004-2097	DRW. HOLS	CHKD:	APPR: PSMITH	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE 8:1	DESIGN UNITS INCH	DIMENSION STYLE IN/MM	THIRD ANGLE PROJECTION	TITLE	REVISE ON CAD ONLY
							mm	INCH						
							4 PLACES ±.005	±.005					CRIMP TERMINAL, FEMALE (1.57)/.062 DIA., BRASS FOR 24 THRU 30 GA. WIRE	MOLEX INCORPORATED
							3 PLACES ±.005	±.01						
							2 PLACES ±0.25	±.014						
							1 PLACE ±0.35	±.014						
							ANGULAR ±1/2°							
							DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS						SEE CHART	SD-1855-*
							THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							