

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Amphenol RF
132220](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

REV.	DATE	DESCRIPTION
NC	01/16/03	INITIAL RELEASE
A	06/11/03	ADD MOUNTING HOLE DIMS.

RECOMMENDED CABLE STRIPPING DIM'S

RECOMMENDED MOUNTING HOLE DIMENSIONS

8 HEX

1.60 [.063]

11.40 [.449]

16.30 [.642]

9.80 [.386]

1.43 [.056]

.60 [.024]

2.70 [.106]

.60 [.024]

5.40 [.213]

10.30 [.406]

1.00 [.039]

1.70 [.067]

4.50 [.177]

6.35 HEX

5.20 [.205]

5.50 [.217]

2.40 [.095]

3.80 [.150]

19.30 [.761]

4.00 [.158]

4.60 [.181]

8	HEAT SHRINK				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.	APPROVALS	DATE	Amphenol Connex							
7	FERRULE	COPPER	GOLD	1	UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.40mm 30 - 120mm ± 0.50mm	DRAWN	G.R.S.	06/11/03	PART DESCRIPTION						
6	HEX NUT	BRASS	GOLD	1	UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 - .315 = ± 0.007" .315 - 1.180 = ± 0.015" 1.180 - 4.724 = ± 0.020"	CHECKED			SMA BULKHEAD CRIMP JACK (FOR RG-178B/U, 196/U CABLE)						
5	BARREL	BRASS	GOLD	1		ISSUED			PART NO.						
4	CONTACT PIN	BRASS	GOLD	1		SHEET	1 OF 1		132220						
3	INSULATOR	TEFLON	NATURAL	1											
2	HOUSING/BODY	BRASS	GOLD	1											
1	DESCRIPTION	MATERIAL	FINISH	QTY	DO NOT SCALE DRAWING	CAD FILE	C:/132/132220.DWG	DWG. NO.	132220.DWG	REV.	A	SIZE	A	SCALE	NA