

Excellent Integrated System Limited



Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[On-Shore Technology, Inc.](#)
[OSTTT020180](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



N=Number of poles



Material

- Terminal body
- (metal housing): Brass(CuZn)
- Terminal screw: Steel Zinc plating "-" slot type
- Wire guard: PhBz, Tin or Au plated.
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 300VAC
- Current rating: 10A
- Wire range:
 - Solid wire(AWG): 16-22
 - Stranded wire(AWG): 16-22
- Torque(Lb-In): 1.7
- Screw: M3
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -30°C to +105°C
- Safety approval: CE, RoHS

RoHS Compliant

PART NUMBER:

OSTTTXX0180

No. of Poles

02: 2 Poles

5: 5 Poles

24: 24 Poles

COLOR

0: Black

5: Green

6: Blue

8: Grey (Standard)



ON-SHORE TECHNOLOGY, INC.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

TITLE		OSTTT - 5.0mm Series	
PART NO.	OSTTTXX0180	DWG NO.	OSTTTXX0180.DWG
APPROVED	Marvin 2006.10.23	CHECKED	Marvin 2006.06.24
DESIGNED	Marvin 2006.06.24	DRAWN	Marvin 2006.06.24
		CUST NO.	
		UNIT:	mm
		SCALE:	NONE
		SHEET:	01/01
		REV:	D
		Tolerance	X ±0.50 X.X ±0.30 X.XX ±0.10 X* ±1*