

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[3M](#)
[3112-1](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Polyethylene Protective Tapes

3110 • 3112 (Clear)

Technical Data

April, 2007

Product Description

3M™ Polyethylene Protective Tapes 3110 and 3112 have a low-tack adhesive system to help provide temporary protection in *general industrial applications* for many polished metals, plastics, glass materials and for many material surfaces that are susceptible to damage caused by abrasion and marring. Since the film may contain small scratches, gels and wrinkles and a slight amount of haziness or visible adhesive coating pattern may be present, it is not recommended for some plastic lens, or similar applications which do not allow such visual imperfections.

Construction

Backing	Adhesive	Colors	Standard Roll Size
Low-density polyethylene	Acrylic	Clear*	48 in. (1200 mm), 60 in. (1500 mm), 72 in. (1800 mm) x 1000 ft. (304.8 m) to 5000 ft. (1524 m)

*Contact your local 3M sales representative for additional information about colors.

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

	Nominal Results		ASTM Test Method
Adhesion to Steel: (oz./in. width)	3M tape 3110 2	3M tape 3112 3	D-3330
Tack Level:	Very Low	Low	
Tensile Strength: (Break or Yield)	2500 PSI / 1.7 MPA		D-882
Elongation: (Break or Yield)	450%		D-882
Total Tape Thickness:	3.0 mils (0.08 mm)		D-3652

Features

- Low-tack adhesive for easy removal to help reduce labor costs.
- Transparent backing allows visual inspection without tape removal to help reduce rework.
- Abrasion resistant backing resists tearing during forming to help reduce labor costs, rejects and reworks.

Application Ideas

- Automotive – trim: bi-metal aluminum-polished gloss, stainless steel, chrome and interior plastic.
- Graphic Arts – nameplates: gloss screenprinted.
- Plastics – gloss high-pressure laminates; sheeting: polished polycarbonate, polyester and acrylic.
- Metals – aluminum: anodized bright specular; stainless steel: 430 bright annealed.
- Architectural Panels and Garage Doors – smooth and painted-gloss.

3M™ Polyethylene Protective Tapes

3110 • 3112 (Clear)

Application Techniques	For optimum performance, these tapes should be applied and removed at a temperature not less than 60°F (16°C). These tapes are not designed for prolonged exposure to direct sunlight for extended periods. Prolonged exposure to heat, moisture and direct U.V. light or sunlight may adversely affect the performance of these tapes and may result in adhesion build-up, high unwind and adhesive residue problems.
Storage	Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.
Shelf Life	To obtain best performance, use this product within 12 months from date of manufacture.
For Additional Information	To request additional product information or to arrange for sales assistance, call toll free 1-800-241-2031 or 828-465-3053. Address correspondence to: PolyMask, a 3M company, 500 Thornburg Dr., P.O. Box 309, Conover, NC 28613. Our fax number is 1-800-672-3038 or 828-465-2404.
Product Use	All statements, technical information and recommendations contained in this document are based upon tests or experience that PolyMask Corporation and 3M believe are reliable. However, many factors beyond the control of PolyMask Corporation and 3M can affect the use and performance of a PolyMask Corporation and 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the PolyMask Corporation and 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.
Warranty and Limited Remedy	Unless stated otherwise in other product literature, packaging inserts or product packaging for individual products, PolyMask Corporation and 3M warrants that each PolyMask Corporation and 3M product meets the applicable specifications at the time PolyMask Corporation and 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. POLYMASK CORPORATION AND 3M COMPANY MAKE NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the PolyMask Corporation and 3M product is fit for a particular purpose and suitable for user's application. If the PolyMask Corporation and 3M product is defective within the warranty period, your exclusive remedy and PolyMask Corporation and 3M's sole obligation will be, at PolyMask Corporation and 3M's option, to replace the product or refund the purchase price.
Limitation of Liability	Except where prohibited by law, 3M Company and PolyMask Corporation, will not be liable for any loss or damage arising from the PolyMask Corporation and 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



ISO 9001:2000

This product was manufactured under a quality system registered to ISO 9001:2000 standards by PolyMask Corporation, a 3M company.

Industrial Business Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
www.3M.com/protectivetapes



Recycled Paper
40% pre-consumer
10% post-consumer

PolyMask Corporation is a 3M Company.
3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2007 70-0709-4944-4 (4/07)