

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Test Products International \(TPI\)](#)
[TLS2000B](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Optional Accessories

TPI offers a complete line of...

Handheld Oscilloscopes

Digital Multimeters

Digital Clamp-on Meters

Gas Detection Instruments

Combustion Analyzers

Refrigeration Leak Detectors

Digital Manometers

Contact and Infrared Temperature Instruments

Oscilloscope Probes

Surface Mount Test Clips

BNC-BNC Molded Coax Cables

F-series Cables

Full Line of Accessories

A103 Protective Boot A403 Protect against impact and wear. Hanging Boot Hook A103 Work hands free with the 440's protective boot and hook.	PC Software & RS232 Cable A402 Download data and waveforms from the 460 to any PC using Microsoft Windows.	Soft Zipper Case A900 Keep your 440, AC/DC charger, test leads and optional accessories at the ready. Movable partitions and adjustable shoulder strap.	Clamp-on Adapters A201 Measure up to 400 AC amps. A206 Measure up to 400 AC/DC amps. A206 Measure up to 2,000 AC/DC amps.	Low Current Adapter A254 Measures from 10mA to 60 amps AC/DC.	Current Shunt Adapter A130 Allows any DMM with AC/DC millivolt range to measure up to 30 amps.
Temperature Adapter A301 Measure -40° to 500° F. For K-type thermocouple probes.	Fused Test Leads FTLK1 Reduce your risk of electrical shocks and/or instrument damage.	High Voltage Probe HV40C Measure up to 40 KV DC.	Test Lead Kits w/Silicone Insulation TLS2000B Shattered plug TLS2000RB Right angle plug	Pressure Adapter A620 Measure up to 500 PSI. A630 Measure up to 10,000 PSI.	Cigarette Lighter DC Adapter A408 Charge the 440 while on the road or in remote locations.



To learn about the entire TPI product line visit www.tpi-thevalueleader.com

Test Products International, Inc. Headquarters: 9615 SW Allen Blvd. Beaverton, OR 97005 USA 503-520-9197 Fax: 503-520-1225 e-mail: info@tpi-thevalueleader.com	Test Products International, Ltd. 342 Bronte St. South Unit #9 Milton, Ontario L9T 5B7 Canada 905-693-8558 Fax: 905-693-0888 e-mail: info@tpicanada.com	Test Products International UK, Ltd. Longley House, East Park Crawley, West Sussex RH10 6AP England +44 (0)1293 561212 Fax: +44 (0) 1293 813465 e-mail: info@tpi-uk.com
--	--	---

Distributed By:



Your Tools at Work

460 Handheld Oscilloscope

Dual Channel, 20MHz Oscilloscope with True RMS DMM.

Technicians appreciate the bright backlight of the 3" x 3" cold cathode fluorescent display and rugged construction inside and out.

New with the 460

- Cursor Readout
- Decibels
- Pre and Post Triggering
- eULS 3111

INCLUDED

Two Test Leads, two Banana to BNC Adapters, one DC-60 MHz x 1 x 10 Passive Oscilloscope Probe, Power Supply and Instruction Manual



TPI 460 Applications

Power Quality

Variable Speed Drives

Industrial Motor Controls

Battery Testing

Programmable Logic Controls

NC/CNC Machines

Uninterruptable Power Supplies

Audio

Video

Industrial Lighting Controls

Factory Automation

Line Conditioners

Voltage Regulators

Inverters

Gaming Industry

See page two for technical information.

The Value Leader™

460 FEATURES

20 MHz Bandwidth

Capture signals from AC/DC drive motors, sensors, actuators, line and control voltages, UPS and industrial machines.

Cursor Readout

Measure the width and amplitude of the signal and display it on the screen instead of trying to figure it out manually.

Decibels

Accurately measure sound signals.

Pre and Post Triggering

View the waveform before and after the point the scope triggers at to find glitches and other anomalies with the signal.

Trend Mode

Graph readings over a predetermined time period to check for surges or dropouts.

Dual Input

View two waveforms on the display for comparison and troubleshooting.

True RMS DMM

Measure AC/DC volts up to 600V, frequency to 20 MHz, and resistance to 20 Meg ohm. Obtain accurate measurements of non-sinusoidal AC voltage and current waveforms found in controls and circuits with True RMS.

Real Time Sample Rate

Capture spikes and dropouts of industrial signals with real time sampling of 25 megasamples per second.

Bright LCD Backlight

Adjust brightness levels for clarity in any light condition.

Optically Isolated RS232 Output

Transfer data safely without a direct connection to your computer's circuitry.

Continuous Autoset

Feature automatically determines the correct vertical and horizontal settings for optimum waveform viewing. Autoset provides hands free operation while moving between test points.

COMPARE	TPI 460	Fluke 123
Screen Size	78mm x 78mm (3" x 3")	72mm x 72mm (2.8" x 2.8")
Backlight LED	cold cathode fluorescent	cold cathode fluorescent
Bandwidth	20MHz	20MHz
Cursor Readout	yes	no
Resolution	5 bit	5 bit
True RMS	yes	yes
Charge	yes	yes
Banana to BNC Adapters (2)	yes	no
DC-60 MHz x 1x10 Probe	yes	yes

The above information is provided to the best of TPI's knowledge and is not guaranteed. The above information is subject to change at any time.



Dual Channel, 20MHz Oscilloscope with True RMS DMM

Specifications and Frequently Asked Questions



Included
 Two Test Leads, two Banana to BNC Adapters, one DC-60 MHz X1 X10 Passive Oscilloscope Probe, Power Supply and Instruction Manual

APPLICATIONS

Industrial motor control View start-up inrush currents, waveform symmetry, SCR trigger pulses, variable frequency drive signals, pulse width modulation, noise, misc. AC/DC speed control signals.

Power quality Noise on industrial feeds, AC voltage waveshape, current waveforms, machine start-up/power quality interference and noise.

Programmable logic controls PLC input and output signals, control signals, signal conditioning circuits, communications lines and power supplies.

NC machines Power quality, sensor outputs, control circuits, safety circuits, calibration and adjustments.

Uninterruptible power supplies Sensing and monitoring circuits, switching circuits, output waveforms and current waveforms.

Technicians appreciate the bright backlight of the 3" x 3" cold cathode fluorescent display and rugged construction inside and out.

Cursor Readout

cULus

FEATURES

20 MHz Bandwidth

Capture signals from AC/DC drive motors, sensors, actuators, line and control voltages, UPS and industrial machines.

Cursor Readout

Allows you to measure the width and amplitude of the signal and display it on the screen instead of trying to figure it out manually.

Decibels

Allows you to accurately measure sound signals.

Pre and Post Triggering

View the waveform before and after the point the scope triggers at to find glitches and other anomalies with the signal.

Trend Mode

Graph readings over a predetermined time period to check for surges or dropouts.

Dual Input

View two waveforms on the display for comparison and troubleshooting.

True RMS DMM

Measure AC/DC volts up to 600V, frequency to 20 MHz, and resistance to 20 Meg ohm. True RMS allows you to obtain accurate measurements of non-sinusoidal AC voltage and current waveforms found in controls and circuits.

Real Time Sample Rate

Capture spikes and dropouts of industrial signals with real time sampling of 25 megasamples per second.

Bright LCD Backlight

Adjust brightness levels for clarity under any light condition.

Optically Isolated RS232 Output

Transfer data safely without a direct connection to your computer's circuitry.

Continuous Autoset

Feature automatically determines the correct vertical and horizontal settings for optimum waveform viewing. Autoset provides hands free operation while moving between test points.

Audio Public address feeds, amplifiers, mixers and preamps.

Video Horizontal and vertical scan rates, z-axis blanking, sync pulses and luminance.

Industrial lighting controls SCR and other solid state designs.

Factory automation Robot control signals, machine vision, machine control and sensing circuits, calibration of positioning systems, analog controllers and servo controls.

Line conditioners Noise and quality.

Voltage regulators Noise and stability.

Inverters Waveform quality.

CERTIFICATION OF CALIBRATION, CERTIFICATE OF COMPLIANCE
 For details and related fees, call 800-368-5719.

SPECIFICATIONS

VERTICAL	
Bandwidth	20 MHz w/SP608 10:1 Probe 10 MHz w/Shielded Test Leads
Sample Rate	25 Megasamples per Second up to 2 MHz
Real Time	500 Megasamples per Second > 2 MHz
Equivalent Time	500 Megasamples per Second > 2 MHz
Sensitivity	50mV to 200V/div 1,2,5 Sequence
Coupling	AC, DC, GND
Resolution	8 bits
Accuracy	± (3% + 0.05 range/div)
HORIZONTAL	
Modes	Single, Normal, Auto
Samples per Division	25
Accuracy	Equivalent Time: ± (0.5% + 0.08 time/div) Real Time: ± (0.1% + 0.04 time/div)
TRIGGER	
Source	Internal
Modes	Free Run, Normal
Sensitivity	Equivalent Time: 3 divisions or more Real Time: 2 divisions or more
TREND MODE	
Plot Time	30 sec/div to 1 hour/div
Plot Data Type	Max/Min Selectable
Memory	2 Screens
TRUE RMS DMM	
DCV (CH1, CH2)	400mV, 4, 40, 400, 600V
Basic Accuracy:	± (0.5% + 5 digits)
ACV (CH1, CH2)	400mV, 4, 40, 400, 600V
Basic Accuracy:	± (1% + 10 digits)
Frequency (CH1, CH2)	1 Hz to 20 MHz
Basic Accuracy:	± (0.5% + 5 digits)
Ohm (CH1 only)	400, 4k, 40k, 400k, 4M, 20M
Basic Accuracy:	± (0.5% + 5 digits)
Continuity (CH1 only)	Sounds < 0.1k ohm, ± (2% + 5 digits)

International Version: 220V 50/60Hz AC/DC adapter is included when specifying model no. 460X.

OPTIONAL ACCESSORIES



Temperature Adapter A201
 Measure -40° to 500° F. For K-type thermocouple probes, refer to pages 18-19.



Pressure Adapter A220
 Measure up to 500 PSI.



Clamp-on Adapters A231, A256, A296
 Measure up to 400 AC amps.
Clamp-on Adapter A256
 Measure up to 400 AC/DC amps.
Clamp-on Adapter A296
 Measure up to 2,000 AC/DC amps.



PC Software & RS232 Cable A404
 Download data and waveforms from the 460 to any PC using Microsoft® Windows®.



Low Current Adapter A254
 Measure below one amp AC/DC.



Current Shunt Adapter A139
 Extend amp range to 30 amps.



Soft Zipper Case A465
 Protect and organize your 460.



Protective Boot A405
 Guard against inevitable impacts. Unique rear cut-out design allows deployment of 460's rear tilt stand.



Surface Mount Test Clips
 Multifurcated clips to access 0.3 pitch leads. See page 26.



High Voltage Probe HV15HFA
 Measure accurately up to 15KV DC. See page 11.



60 MHz Oscilloscope Probe
 Three monolithic interchangeable probes in 60, 100, and 250 MHz bandwidth. See page 25.

FAQ

Why do you need a 20 MHz oscilloscope?

To measure signals and voltage anomalies, and to look for glitches that may damage or even shut down electronic machinery. View sine waves on power supplies, motors, and board circuitry. Pinpoint certain glitches on the sine wave to zero in on the problem and monitor changing patterns or distortion in electrical currents.

What are the different waveform patterns displayed on your handheld oscilloscopes?

An AC waveform known as **sine wave** displays voltage against time in the shape of a sine curve. The **saw tooth** waveform displays a ramped angle and a sharp downward return to its earlier value. (Its display pattern resembles the cutting edge of a saw.) A **square waveform** graphically plots a series of vertical square shapes repeated with spacing between peaks.

Why is it important to have Trend Mode?

Trend Mode is great for monitoring sudden intermittents caused by loose connections, dirt, or damaged wires. By setting the minimum and maximum parameters, you can monitor, even record the changes.

What is the purpose of triggering?

Simply zoom in on certain parts of the sine wave and "hold" to measure and monitor that particular part you are reading. A must have when searching for glitches and distortion on all measurements.