

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Schurter](#)  
[6051.2037](#)

For any questions, you can email us directly:



[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

**Cord Sets**

[www.schurter.com/PG07\\_2](http://www.schurter.com/PG07_2)

IEC Interconnection Cord with IEC Connector C13, V-Lock, straight

**new**



**Description**

- Interconnection Cord,
- Protection class I, Pin temperature 70 °C,
- with V-Lock interlocking system

**Technical Data**

|                           |   |           |   |
|---------------------------|---|-----------|---|
| Ratings IEC               | 10A / 250VAC; 50Hz  | Connector | C13 acc. to IEC 60320-1 IEC 60320-1   |
| Dielectric Strength       | > 2kVDC between L-N<br>> 2kVAC between L/N-PE<br>(1 min/50Hz)     |           | UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 10A, Protection Class I |
| Allowable Operation Temp. | -25 °C to 70 °C   |           |   |
| Degree of Protection      | from front side IP 20 acc. to IEC 60529                           |           |   |
| Protection Class          | Suitable for appliances with protection class I acc. to IEC 61140 |           |   |
| Terminal                  | moulded   |           |   |
| Material: Housing         | PVC, black  |           |   |

**All Variants**

| Connector |        | cable         |                          |            |       | Plug            |         |               |          |       | Order Number |
|-----------|--------|---------------|--------------------------|------------|-------|-----------------|---------|---------------|----------|-------|--------------|
| Type      | V-Lock | Cord Type     | Conductor cross section  | Length [m] | Color | Type            | Country | Standard      | Style    | Index |              |
| C13       | ●      | H05VV-F3G0.75 | 3 x 0.75 mm <sup>2</sup> | 0.6        | black | Interconnection | INT     | IEC 60320-2-2 | straight | -     | 6051.2037    |

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/Stock-Check/Stock-Check-SCHURTER>

**Packaging unit** 150 Pcs

**Mating Outlets/Connectors**

Category / Description



[Appliance Outlet Overview complete](#)

|   |        |
|---|--------|
| IEC Appliance Outlet F, Screw-on Mounting, Front Side, Solder or Quick-connect Terminal   | 6600-3 |
| IEC Appliance Outlet F, Snap-in Mounting, Front Side, Solder or Quick-connect Terminal  | 6600-4 |
| 6602-4, Mounting: Snap-in version, Appliance Outlet: IEC H, Solder terminals or quick connect terminals, 10 A, Suitable for appliances with protection class II | 6602-4 |
| IEC Appliance Outlet F, Snap-in Mounting, Front Side, IDC Terminal  | 6610   |

[Appliance Outlet further types to 6051.2037](#)

Mating Inlets/Plugs shuttered

Appliance Inlet Overview complete



|  |      |
|--|------|
| 6010, Mounting: Snap-in, Solder, quick-connect, screw, PCB, Appliance Inlet: IEC C14   | 6010 |
| IEC Appliance Inlet C18, Snap-in Mounting, Solder, Quick-connect, Screw- or PCB Terminal   | 6015 |
| 6048, Mounting: Screw, Appliance Inlet: IEC C14  | 6048 |
| 6061, Mounting: Screw, Appliance Inlet: IEC C14  | 6061 |
| GSP1, Mounting: Screw, Appliance Inlet, IEC C14, For PCB mounting, IP 40, Quick connect terminals 4.8 x 0.8 mm angled or straight, Suitable for appliances with protection class I or II | GSP1 |
| Appliance Inlet further types to 6051.2037   | ...  |

Power Entry Module Overview complete



|  |      |
|--|------|
| DC11, Mounting: Screw, Rocker switch: non-illuminated or illuminated 1 or 2 pole, Quick connect terminals 4.8 x 0.8 mm, Appliance Inlet: IEC C14, Without fuse holder: Suitable for appliances with protection class I or II   | DC11 |
| DC21, Mounting: Screw Rear Side, Rocker switch: non-illuminated or illuminated 2-pole, Quick connect terminals 4.8 x 0.8 mm Appliance Inlet: IEC C14, Without fuse holder:   | DC21 |
| DD11, Mounting: Screw-on mounting, Rocker switch: non-illuminated or illuminated 2-pole, Quick connect terminals 4.8 x 0.8 mm, Appliance Inlet: IEC C14, With or without protection cover, Fuse holder: 1 or 2 pole, Suitable for appliances with protection class I | DD11 |
| DD21, Mounting: Screw-on mounting Rear Side, Rocker switch: non-illuminated or illuminated 2-pole, additional quick connect 4.8 x 0.8 mm Appliance Inlet: IEC C14, Fuse holder: 1 or 2 pole  | DD21 |
| KD, Mounting:Screw, Quick connect terminals 4.8 x 0.8 mm, voltage selector: 2-4 digits, Fuse holder: 1 or 2 pole, Rocker switch, non-illuminated, 2-pole, Appliance Inlet: IEC C14, 250 VAC, prewired, Suitable for appliances with protection class I               | KD   |
| Power Entry Module further types to 6051.2037  | ...  |

Power Entry Module with line filter Overview complete



|  |      |
|--|------|
| DC12, Mounting: Screw, Front-/Rear-Side, Filter, Standard and Medical Version, Without fuse holder:10 A, Rocker switch: 1 or 2 pole, non-illuminated or illuminated Appliance Inlet: IEC C14, prewired                                       | DC12 |
| DC22 Mounting: Screw, Rear Side, PCB, 10 A, Filter: Standard and Medical Version, Without fuse holder: Rocker switch: 1 or 2 pole, non-illuminated or illuminated, Appliance Inlet: IEC C14, Suitable for appliances with protection class I | DC22 |
| DD12, Mounting: Screw-on mounting, Front Side, Filter, Standard and Medical Version, Fuse holder:1 or 2 pole, 10 A, Rocker switch: 2-pole, non-illuminated Appliance Inlet: IEC C14, prewired  | DD12 |
| DD22 Mounting: Screw-on mounting, Rear Side, PCB, 10 A, Filter: Standard and Medical Version, Fuse holder: 1 or 2 pole, Rocker switch: 2-pole, non-illuminated, Appliance Inlet: IEC C14, Suitable for appliances with protection class I    | DD22 |
| CD, Mounting: Screw, Front Side, Filter: Standard and Medical Version, Fuse holder: 1 or 2 pole, Front Side, 10 A, 2-pole, voltage selector: step, 2-4 digits, Appliance Inlet: IEC C14, prewired  | CD   |
| Power Entry Module with line filter further types to 6051.2037   | ...  |