

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2800461](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online
catalog

VAL-SQ SP 100-120/208Y

Order No.: 2800461



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2800461>

Surge protection device for 120/208 V AC Wye configurations.
Uses a compact, NEMA rated enclosure that connects easily to an
existing enclosure. Hybrid Sine Wave Tracking provides 100 kA surge
protection.

Commercial data

GTIN (EAN)	 4 046356 564953
Note	Made-to-order
sales group	J102
Pack	1 pcs.
Customs tariff	85363090
Catalog page information	Page 76 (TT-2011)

Product notes

WEEE/RoHS-compliant since:
02/21/2010



[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Product description

Surge protective device for 120/208 V AC and 127/220 V AC Wye systems with 100 kA protection

VAL-SQ SP 100-120/208Y Order No.: 2800461
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2800461>

Technical data

Standards

Degree of protection	NEMA 4X
Mounting type	3/4 inch NPT male
Design	Parallel hybrid
Ambient temperature (operation)	-40 °C ... 71 °C
Ambient temperature (storage/transport)	-40 °C ... 65 °C
Altitude	3658 m
Message: Surge protection fault	Phase LEDs
	Audible alarm
	Remote indicator contact
Direction of action	3L-N & N-GND
Width	250.00 mm
Height	122.00 mm

Protective circuit

Arrester rated voltage U_c	150 V
Response time	< 1 ns

Connection, protective circuit

Connection method	#10 AWG/5.26 mm ² wires (24 in./61 cm long)
	4-wire + Gnd
Conductor cross section AWG/kcmil min.	10
Conductor cross section AWG/kcmil max	10

Remote indicator contact

Connection method	#24 AWG/0.205 mm ² wires (24 in./61 cm long)
-------------------	---

NEMA / UL data

UL type	type 2
Maximum Continuous Operating Voltage (MCOV without reference direction)	150 V
Voltage protection rating (VPR L-L)	1500 V
Voltage protection rating (VPR L-N)	900 V
Voltage protection rating (VPR L-PE)	1200 V
Voltage protection rating (VPR N-PE)	700 V

VAL-SQ SP 100-120/208Y Order No.: 2800461

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2800461>

Nominal discharge current I_n (without reference direction)	20 kA
Maximum Surge Current per Phase	100 kA
Short-circuit current rating (SCCR)	200 kA
EMI/RFI filtering	-30 dB @ 100 kHz

Environmental conditions

Standards/regulations	UL 1449 3 rd edition, Sept. 2009
	UL 1283
	IEEE C62.41
	IEEE C62.45

VAL-SQ SP 100-120/208Y Order No.: 2800461
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2800461>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;