

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Orion Fans](#)

[OSP-H15-11-08-N1](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

MODEL:
Switched PDU



MODEL NUMBER:
OSP-H-15-11-08-N1



Features

| | |
|------------------|---|
| Current Meter | Digital True RMS Current Meter |
| Power Monitor | Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software |
| Protocols | http, https, SNMP, DHCP, UDP |
| Outlet Control | Individual Outlet Control |
| Power Delay | Power On/Off Sequence can be Defined |
| Alarm Thresholds | User-Defined Alarm Thresholds for Warning and Overload |
| Event Alert | Email, Trap, Audible Alarm |

Specification:

| General | Communication | Operation |
|--|---|---|
| Output: (8) NEMA 5-15/20R Input: (1) IEC320 C20 Inlet; IEC320 C19 to NEMA 5-15P Power Cord 3 Meters long Protection (1) 15 Amp Circuit Breaker | SSL Indication (1) Yellow LED DHCP Indication (1) Green LED Output Status (8) Green LED Network (1) RJ45 for Ethernet Current Meter 3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20A Resolution: 0.1A Precision: +/-2%/+/-0.1 Amp | Nominal Voltage 115V Voltage 100V~127V full range Frequency 50/60HZ full range Max. Output Current 15 Amp (UL derated 12 Amp) Temperature 0 ~ 40 Celsius degree Humidity 0% ~ 90% Size 90 x 432 x 44 mm Weight 2 kg |

Regulatory Approvals:

UL 60950-1, UL Listed, CSA, cUL Listed, CB by UL
 CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
 FCC Part 15 Class A, ICES-003