

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)


## SMT "AUTO" BLADE FUSE HOLDERS

- Compatible with most vacuum and mechanical pick and place assembly systems.
- Fully insulated clips to protect fuses against shorting.
- One piece assembly reduces assembly time
- Withstands shock and vibration.

AVAILABLE ON TAPE AND REEL




### 2 in 1 FUSE HOLDER



**For Standard:** Littelfuse: ATOF series/ Bussmann ATC series.



**For Low Profile:**  
Littelfuse: 891 series/  
Bussmann ATM-LP series



### SPECIFICATIONS


**Contacts:** .016 (.41) Brass, Matte Tin Plate  
**Insulator:** High Temperature Nylon 46, UL 94V-0  
**UL Temperature Rating:** -58°F to +292°F (-50°C to +145°C)  
**UL Current Rating:** 20 Amps @ 500V AC

**CAT. NO. 3587** (Bulk)



**CAT. NO. 3587TR** (Tape & Reel)

**Tape & Reel Spec's:** 32mm wide, 16mm pitch, 13 inch reel (500 pieces per reel)


### Mounting Detail



### MINI FUSE HOLDER



**For Mini:** Littelfuse: MIN series/Bussmann ATM series or equivalent



### SPECIFICATIONS

**Contacts:** .016 (.41) Brass, Matte Tin Plate  
**Insulator:** High Temperature Nylon 46, UL 94V-0  
**UL Temperature Rating:** -58°F to +292°F (-50°C to +145°C)  
**UL Current Rating:** 20 Amps @ 500V AC

**CAT. NO. 3588** (Bulk)

**CAT. NO. 3588TR** (Tape & Reel)


**Tape & Reel Spec's:** 32mm wide, 16mm pitch, 13 inch reel (500 pieces per reel)

## SMT "AUTO" BLADE FUSE CLIPS


- Compatible with most vacuum and mechanical pick and place assembly systems.
- Accepts standard and mini blade automotive blade fuses.
- Clip with Matte-Tin plate is ideal for low temperature soldering applications, for other temperature sensitive components.
- Clips with Tin-Nickel plate are ideal for lead free, high temperature soldering applications.

### VERTICAL ENTRY

**For Mini:** Littelfuse: MIN series/Bussmann ATM series.  
**For Standard:** Littelfuse: ATOF series/Bussmann ATC series.  
**For Low Profile:** Littelfuse: 891 series/Bussmann ATM-LP series



### Pad Layout For Two Clips



### SPECIFICATIONS

**Material:** .016 (.41) Brass, Tin-Nickel Plate  
**UL Current Rating:** 30 Amps @ 500V AC


**CAT. NO. 3586** (Bulk)

**CAT. NO. 3586TR** (Tape & Reel)


**Tape & Reel Spec's:** 16mm wide, 12mm pitch, 13 inch reel (750 pieces per reel)

### VERTICAL ENTRY

**For Mini:** Littelfuse: MIN series/Bussmann ATM series or equivalent



### Pad Layout For Two Clips



### SPECIFICATIONS

**Material:** .016 (.41) Brass, Matte Tin Plate  
**UL Current Rating:** 15 Amps @ 500V AC



**CAT. NO. 3563** (Bulk)

**CAT. NO. 3563TR** (Tape & Reel)


**Tape & Reel Spec's:** 24mm wide, 12mm pitch, 13 inch reel (1500 pieces per reel)

### HORIZONTAL ENTRY

**For Mini:** Littelfuse: MIN series/Bussmann ATM series or equivalent



### Mounting Detail For Two Clips



### SPECIFICATIONS

**Material:** .012 (.30) Brass, Tin-Nickel Plate  
**UL Current Rating:** 20 Amps @ 500V AC

**CAT. NO. 3569** (Bulk)

**CAT. NO. 3569TR** (Tape & Reel)

**Tape & Reel Spec's:** 24mm wide, 8mm pitch, 13 inch reel (1000 pieces per reel)