

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Honeywell Sensing and Productivity Solutions](#)
[V3-23-B](#)

For any questions, you can email us directly:


sales@integrated-circuit.com

MICRO SWITCH
 a Honeywell Division
 FED.MFG.CODE 91929

SWITCH - BASIC

CATALOG LISTING
V3-23-B
CK-A2310

CATALOG LISTING
V3-23-B
 PAGE 1 OF 1
 RELEASE NO. SR-10128
 REPLACES
 CHECK
 12
 ISSUE
 REVISIONS
 A CO-80609 DCS 26 JUL 95
 B CO-80957 DCS 24 OCT 95
 DDC/CAD
 DRAWN
 DCS 26 JUL 95
 CHECK
 DCS 26 JUL 95



NOTES

- 1 TERMINAL SCREW (PART NO VP-10320) AND LOCKWASHER (PART NO VP-14672), TWO EACH, FURNISHED UNASSEMBLED, BULK PACKED
- 2 - MARK CATALOG LISTING "V3-23" ON SWITCH-OMIT THE "B"
- 3 - USE COMPLETE CATALOG LISTING "V3-23-B" ON ALL PACKAGING MATERIAL

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL	DO NOT SCALE PRINT
OPERATING FORCE — — — — 6-14 OZ	CONTACT ARRANGEMENT S P N O	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
RELEASE FORCE — — — — 4 OZ MIN	L83 15.1A 1/2HP 125, 250 VAC 1/2A 125 VDC, 1/4A 250 VDC 5A 125 VAC "L"	ONE PLACE (.0)	± .030
DIFFERENTIAL TRAVEL — — .006-.016		TWO PLACE (.00)	± .015
OVERTRAVEL — — — — .040 MIN		THREE PLACE (.000)	± .005
FREE POSITION — — — — .625 MAX		ANGLES	±
RELEASE TRAVEL — — — — .007 MIN	WEIGHT .016 LB		

