

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[LEMO](#)
[XAN.M13.GLA.6G](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

SUMMARY

Wires

Low	13
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0



Download

[Request a quote](#)

[Catalog](#)

Series

Termination type	Male solder
IP rating	50
Cable Ø	5.30 - 6.50 mm
Matching parts	xxx

TECHNICAL DETAILS

Mechanics

Shell Style/Model	XA*: Straight plug, key (N) or keys (P, S and T), with grey cable collet
Keying	3 key (alpha=30, plug: male contacts, receptacle: female contacts)
Housing Material	
Cable Fixing	∅ 5.3 - 6.5 mm
Variant	G : Gray collet nut

Performance

Configuration	M13 : 13 Low Voltage
Insulator	L: PEEK
Rated Current	

Specifications


Test voltage (kV rms) Contact-contact: 1.05
 Air clearance min. (mm) or Creepage distance min. (mm): 0.5

Others

F ret (average): 130 N
 Working temperature: -50 deg C to + 170 deg C
 IP Rating: 50

DRAWINGS

Draws



Dimensions

	A	L
mm.	16.5	46
in.	0.65	1.81

RECOMMENDED BY LEMO

Tools

Crimp Tool: DPC.91.701.V

Cables