

# **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Honeywell Sensing and Productivity Solutions 236PC100GW

For any questions, you can email us directly: <a href="mailto:sales@integrated-circuit.com">sales@integrated-circuit.com</a>



# Honeywell

### **Honeywell Sensing and Control**

Home> Products > Piezoresistive Silicon> 236PC> Product Page

#### ■ Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

#### 236PC100GW



Actual product appearance may vary.

Temperature compensated for span

over 0 °C to 50 °C [32 °F to 122 °F]

Calibrated null and span

**Pressure Sensors: Measurement** Type: Gage, Vacuum Gage; Unamplified; Range: ± 100 psi

#### **Potential Applications**

#### Medical

Oxygen and nitrogen gas distribution in hospitals

Respirators and ventilators

#### **Environmental**

Water control valves Instrumentation Irrigation equipment

#### **Industrial Instrumentation**

Robotics Pressure valves Leak detection Air compressors

### Description

**Features** 

Prewired

Robust package

236PC Series pressure sensors provide a millivolt output that is proportional to the pressure applied. They operate from 0 psi to 5.0 psi and 0 psi to 150 psi using a single, positive supply voltage ranging from 10.0 Vdc to 16.0 Vdc.

#### **Supporting Documentation**

#### Engineering **Drawing**

Product Specifications	
Signal Conditioning	Unamplified
Pressure Range	± 100 psi
Maximum Overpressure	225 psi
Supply Voltage	10 Vdc typ., 16.0 Vdc max.
Compensated	No
Output Calibration	Yes
Response Time	1 ms max.
Port Style	Threaded 1/4 - 28 UNF
Package Style	Honeywell - 200PC
Typical Sensitivity	1 mV/psi
Full Scale Span	100 mV typ.
Null Offset	0 mV typ.
Null Shift over Temperature	± 3.0 mV typ.
Repeatability & Hysteresis Error	± 0.25 % span typ.
Shock	Qualification tested to 150 g



Login to iCOM Login as Rep/AD Login as Guest Login to Digital University

#### **Keyword Search**

Search for product and support information.

All Sensing and Contro

#### **Product Search**

Part number search:

Use (\*) to expand search

**Specification Search**