

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[US-Lasers, Inc.](#)  
[D7805I](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

## US-Lasers: 780nm-5mW - Infrared Laser Diodes

[Back to Laser Diodes](#)

**INFRARED DIODE LASER DATA SHEETS**
**ABSOLUTE MAXIMUM RATINGS - (Tc=25 °C)**

<b>TECHNICAL DATA</b> <ul style="list-style-type: none"> <li>Index Guided MQW Structure</li> <li>Wavelength: 780nm (Typ.)</li> <li>Optical Power: 5mW CW</li> <li>Threshold Current: 25mA (Typ.)</li> <li>Standard Package: 5.6mm</li> </ul>		
Infrared light output	780nm	<b>Pin Out Diagram - Style A</b>
Optical power output	5mW CW	
Package Type	5.6mm	
Built-in photo diode for monitoring laser output		

Items	Symbols	Values	Unit
Optical output power	Po	5	mW
Laser diode reverse voltage	VLDR	2	V
Photo diode reverse voltage	VPDR	30	V
Operating temperature	Topr	-10 ~ +40	°C
Storage temperature	Tstg	-40 ~ +85	°C

<b>OPTICAL and ELECTRICAL CHARACTERISTICS - (Tc=25 °C)</b>							
Items	Symbols	Min.	Typ.	Max.	Unit	Test Condition	
Optical output power	Po	-	5	-	mW	-	
Threshold current	Ith	15	25	40	mA	-	
Operating current	Iop	25	35	50	mA	Po=5mW	
Operating voltage	Vop	1.9	2.1	2.5	V	Po=5mW	
Lasing wavelength	8 D	770	780	790	nm	Po=5mW	
Beam divergence	θ F	8	11	15	deg	Po=5mW	
Beam divergence	θ z	20	35	45	deg	Po=5mW	
Slope Efficiency (mW/mA)	0	0.1	0.3	0.6		-	
Monitor current	Im	100	200	600	μ A	Po=5mW, Vr=5V	
Astigmatism	As	-	11	-	μ m	Po=5mW	
MTTF			3000-5,000 hrs.			Po=5mW, NA=0.4	
Emitter Size	1 x 4 Microns						
Emitter Distance to Cap Lens Structure	0.3mm						
	Index Guided						