

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Visual Communications Company, LLC](#)
[5630D5](#)

For any questions, you can email us directly:

sales@integrated-circuit.com




engineered to light up your design

www.vcc-lite.com

1.800.522.5546

5630 Series 2 X 5 Rectangular LED Assembly

Description and Features



Features

- Block mounting, low profile design, height & space alignment - saves assembly costs.
- Super Brite LEDs
- Standoffs prevent flux entrapment.
- Low current-only 2 mA needed.
- Built-in resistor chip-operates directly off 5 Volt supply without external resistor.

Housing: Black Nylon, UL94V-O

Note: Alternate LEDs are also available in this package as a standard variation.

Refer to "Mounting Hole Pattern 2.pdf"

Electro-Optical Characteristics and Ratings

Part Number	Emitted Color	Typical Intensity (mcd)	Rated Current (mA)	Continuous Forward Current Max. (mA)	Forward Voltage		Reverse Breakdown Voltage Min. (V)	Peak Wavelength (nm)	Peak Forward Current at 1MS-300 PPS (A)
					Typ. (V)	Max. (V)			
5630D1	Red	4	20	35	2.0	3.0	5	635	.1
5630D5	Green	4	20	30	2.2	3.0	5	562	.09
5630D7	Yellow	4	20	35	2.1	3.0	5	585	.1