

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:






[Molex Connector Corporation](#)
[0026603118](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

CKT	DIM. A	DIM. B
2	7.77	3.96±0.05
3	3.06	.56±.002
4	11.73	7.92±0.08
5	.462	.312±.003
6	15.70	11.89±0.08
7	.678	.468±.003
8	19.66	15.35±0.10
9	.774	.624±.004
10	23.62	19.81±0.10
11	.930	.780±.004
12	27.58	23.77±0.10
13	1.086	.936±.004
14	31.55	27.74±0.13
15	1.242	1.092±.005
16	35.51	31.70±0.13
17	1.398	1.248±.005
18	39.47	35.66±0.13
19	1.554	1.404±.005
20	43.43	39.62±0.15
21	1.710	1.560±.006
22	47.40	43.59±0.15
23	1.866	1.716±.006
24	51.36	47.55±0.15
25	2.022	1.872±.006
26	55.32	51.51±0.18
27	2.178	2.028±.007
28	59.28	55.47±0.18
29	2.334	2.184±.007
30	63.25	59.44±0.18
31	2.490	2.340±.007
32	67.21	63.40±0.20
33	2.646	2.496±.008
34	71.17	67.36±0.20
35	2.802	2.652±.008

- NOTES:
1. MATERIAL: HEADER-GLASS FILLED POLYESTER, 94V-0, MOLDED NATURAL (WHITE).
2. FINISH:
(154) OVERALL TIN: 0.00254/.000100 MIN OVER 0.00127/.000050 MIN NICKEL.
(197) OVERALL REFLOWED MATTE TIN: 0.00152/.000060 MIN.
OVER 0.00127/.000050 MIN NICKEL OVERALL.
(208) SELECT GOLD: 0.00038/.000015 MIN, SELECT TIN: 0.00254/.000100 MIN.
OVERALL NICKEL UNDERPLATE: 0.00127/.000050 MIN.
(228) SELECT GOLD: 0.00076/.000030 MIN, SELECT TIN: 0.00254/.000100 MIN.
OVERALL NICKEL UNDERPLATE: 0.00127/.000050 MIN.
(241) SELECT GOLD: 0.00051/.000020 MIN.
SELECT TIN: 0.00254/.000100 MIN.
OVERALL NICKEL UNDERPLATE: 0.00127/.000050 MIN.
3. PRODUCT SPECIFICATION AND PROCESS PARAMETERS: SEE PS-08-50.
4. PACKAGING: SEE CHART
5. SOLDERABILITY: PER SMES-152.
6. PIN PUSH-OUT FORCE: PRIOR TO SOLDERING, A 3 LB. MINIMUM FORCE (IN EITHER DIRECTION)
7. PARTS ARE STACKABLE END TO END ON 3.96/.156 CENTERS.
8. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.



2-*	M1
1	M1
SHEET	REV

ADD 41772-0682
EC NO: UCP2012-3876
DRAWN/PPR 2012/05/25
CHKD/BELL 2012/05/25
APPR/SMITH 2012/06/20
M1

QUALITY SYMBOLS
▽=0
▽=0
▽=0
DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)	
	mm
4 PLACES	±.005
3 PLACES	±.010
2 PLACES	±.025
1 PLACE	±.038
ANGULAR ±1/2°	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE	
MM/IN	
DRAWN BY	DATE
SCHAFER	11-19-03
CHECKED BY	DATE
SAMIEC	11-21-03
APPROVED BY	DATE
MARGULIS	11-25-03
MATERIAL NO.	
SEE CHART	
SIZE	B

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
2:1	INCH	
TITLE		
KK 156 HEADER ASSEMBLY FLAT RIGHT ANGLE SOLID BODY W/O PEGS		
MOLEX INCORPORATED		
DOCUMENT NO.		
SDA-41772		
SHEET NO.		
1 OF *		