

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Molex Connector Corporation](#)
[0026615180](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

NOTES:

1. MATERIAL: HEADER-GLASS FILLED POLYESTER, 94V-0, MOLDED NATURAL (WHITE).
2. FINISH: (197) AROUND REFLOWED MATTE TIN. 0.00152/.00060 MM.
OVER 0.000127/.000050 MM. NICKEL. OVERLAY:
(154) OVERALL TIN: .00254/.000100 MM. OVER .000127/.000050 MM. NICKEL.
(238) SELECT GOLD: .00038/.000100 MM. SELECT TIN: .00254/.000100 MM.
OVERALL NICKEL UNDERPLATE: .00127/.000050 MM.
(228) SELECT GOLD: .00076/.000030 MM. SELECT TIN: .00254/.000100 MM.
OVERALL NICKEL UNDERPLATE: .00127/.000050 MM.
(14) OVERALL GOLD: .00051/.000020 MM.
SELECT TIN: .00254/.000010 MM.
OVERALL NICKEL UNDERPLATE: .00127/.000050 MM.
FOR ADDITIONAL PLATING INFO, SEE SPDS-88.
3. PRODUCT SPECIFICATION AND PROCESS PARAMETERS: SEE PS-08-50.
4. PACKAGING INFORMATION: SEE CHART
5. SOLDERABILITY: PER SPS-52.
6. PIN PUSH-OUT FORCE: PRIOR TO SOLDERING, A 3 LB. MINIMUM FORCE (IN EITHER DIRECTION).
7. PARTS ARE STACKABLE END TO END ON 396/156 CENTERS.
8. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.
9. SLOTS ON BACKWALL ARE BETWEEN CIRCUTS. SEE CHART FOR LOCATION.
10. CIRCUT 12 IS A VOID LOCATION. VOID LOCATION. CIRCUT 1 MAY OR MAY NOT LINE UP WITH CIRCUT 10 ON THE MATING HOUSING.



DESIGN UNITS INCH	 THIRD ANGLE PROJECTION
.156 HEADER ASSEMBLY FRICTION LOCK RIGHT ANGLE W/O PEGS molex	
SDA-41792	SHEET NO. 1 OF *