

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Panduit](#)

[P14-10R-C](#)

For any questions, you can email us directly:


[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Ring Terminal, Non-Insulated

- Ring tongue design assures a secure connection in high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Brazed seam protects terminal barrel from splitting during the crimp process

- Barrel of terminal internally beveled to provide quick and easy wire insertion
- Maximum recommended operating temperature 302°F (150°C)
- UL and CSA rated up to 2000 V per UL 486A/B, where applicable



Part Number	Wire Range		Stud Size		Length		Width		Clearance		Panduit Crimping Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	AWG	mm <sup>2</sup>	In.	mm	In.	mm	In.	mm	In.	mm			
P14-8R-C	18 – 14 AWG	1.0 – 2.5	#8	M4	0.71	18.0	0.31	7.9	0.25	6.4	CT-100A‡, CT-200‡, CT-600-A‡, CT-1570‡, CT-2500‡	100	1000
P14-10R-C			#10	M5	0.71	18.0	0.31	7.9	0.25	6.4		100	1000
P14-14R-C			1/4"	M6	0.91	23.1	0.46	11.7	0.38	9.7		100	1000
P14-56R-C			5/16"	M8	0.91	23.1	0.46	11.7	0.38	9.7		100	1000
P14-38R-C			3/8"	M10	1.0	25.4	0.53	13.5	0.43	10.9		100	1000
P14-12R-L			1/2"	M12	1.20	30.5	0.72	18.3	0.53	13.5		50	500
P10-8R-L	14 – 10 AWG	2.5 – 6.0	#8	M4	0.78	19.8	0.31	7.9	0.31	7.9	CT-100A‡, CT-200‡, CT-600-A‡, CT-1570‡, CT-1701‡, CT-2500‡	50	500
P10-10R-L			#10	M5	0.81	20.6	0.38	9.7	0.31	7.9		50	500
P10-14R-L			1/4"	M6	0.96	24.4	0.52	13.2	0.38	9.7		50	500
P10-56R-L			5/16"	M8	0.96	24.4	0.52	13.2	0.38	9.7		50	500
P10-38R-L			3/8"	M10	1.05	26.7	0.58	14.7	0.44	11.2		50	500
P10-12R-L			1/2"	M12	1.20	30.5	0.72	18.3	0.53	13.5		50	500
P8-10R-Q	8 AWG	10.0	#10	M5	1.14	29.0	0.47	11.9	0.43	10.9	CT-1701‡, CT-2600 with Die Insert CD-2600-8‡	25	250
P8-14R-Q			1/4"	M6	1.14	29.0	0.47	11.9	0.43	10.9		25	250
P8-56R-Q			5/16"	M8	1.25	31.8	0.59	15.0	0.51	13.0		25	250
P8-38R-Q			3/8"	M10	1.25	31.8	0.59	15.0	0.51	13.0		25	250
P8-12R-Q			1/2"	M12	1.36	34.5	0.82	20.8	0.54	13.7		25	250
P6-10R-E			6 AWG	16.0	#10	M5	1.21	30.7	0.47	11.9		0.43	10.9
P6-14R-E	1/4"	M6			1.21	30.7	0.47	11.9	0.43	10.9	20	200	
P6-56R-E	5/16"	M8			1.33	33.8	0.62	15.7	0.51	13.0	20	200	
P6-38R-E	3/8"	M10			1.33	33.8	0.62	15.7	0.51	13.0	20	200	
P6-12R-E	1/2"	M12			1.43	36.3	0.82	20.8	0.51	13.0	20	200	
P4-14R-E	4 AWG	25.0			1/4"	M6	1.40	35.6	0.55	14.0	0.50	12.7	CT-1701‡, CT-2600 with Die Insert CD-2600-4‡
P4-56R-E			5/16"	M8	1.46	37.1	0.68	17.3	0.50	12.7	20	200	
P4-38R-E			3/8"	M10	1.46	37.1	0.68	17.3	0.50	12.7	20	200	
P4-12R-E			1/2"	M12	1.55	39.4	0.86	21.8	0.53	13.5	20	200	
P2-14R-X	2 AWG	35.0	1/4"	M6	1.46	37.1	0.68	17.3	0.58	14.7	CT-1701‡, CT-2600 with Die Insert CD-2600-4‡	10	100
P2-56R-X			5/16"	M8	1.46	37.1	0.68	17.3	0.58	14.7		10	100
P2-38R-X			3/8"	M10	1.46	37.1	0.68	17.3	0.58	14.7		10	100
P2-12R-X			1/2"	M12	1.55	39.4	0.86	21.8	0.58	14.7		10	100

‡UL and CSA approved tooling/product combinations. For crimping tool information, see page M.46 of SA-NCCB51. For the full selection of Panduit Crimping Tools see www.panduit.com.

A. System Overview

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

N. Industrial

O. Labeling & Identification

P. Cable Management Accessories

Q. Index