



Distributor of Harting: Excellent Integrated System Limited

Datasheet of 09642117800 - D-Sub Connector Receptacle, Female Sockets 15 Position Free Hanging (In-Line) Solder Cup

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)

[09642117800](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Technical drawing showing dimensions for the D-Sub connector receptacle:

- Overall length: 33,3 ± 0,2
- Pin pitch: 0,25
- Pin diameter: ϕ 3,1
- Shell thickness: 2,77
- Shell width: 24,6 ± 0,2
- Shell height: 7,9 ± 0,3
- Shell depth: 6 ± 0,3
- Shell diameter: 2,84
- Internal length: 39,2 ± 0,3
- Internal width: 27,7 ± 0,3

FREQUENCY (MHz)	ATTENUATION (dB)
5	0,5
10	1
50	2,5
100	3
500	3,5
1000	4

Operating voltage < 250 V AC
 Working current < 7,5 A
 Insulation resistance > 1GΩ
 Contact resistance < 15 mΩ
 Dielectric withstanding voltage 500 V AC / minute

Solder bucket termination inner diameter: 1,20 mm

09 64 211 7800	PL3
Part number	Performance level

			Det.	Name	 All Dim. in mm Orig. Size DIN A 4	D-Sub, female, straight, 15 poles, tin plated shell, solder buckets, ferrite filter	Maßstab/ Scale 1,5:1	
			Detail.	11/06/09				PK
			Insp.					
			Stand.					

36160	22/09/10	SC	HARTING EURL F-95972 Paris		TB 09 64 211 7800	Blatt / Page 1 / 1
EC00332	11/06/09	PK				
Mod.	Det.	Name	Sub.			