



Distributor of Harting: Excellent Integrated System Limited

Datasheet of 09643217210 - D-Sub Connector Plug, Male Pins 25 Position Free Hanging (In-Line) Solder Cup

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)

[09643217210](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

5
4
3
2
1

Dimensions:
 Total length: 53 ± 0,4
 Length to hole: 47,04 ± 0,15
 Hole diameter: $\phi 3,1 \pm 0,1$
 Hole offset: 8,2 ± 0,2
 Pin length: 12,5 ± 0,4
 Pin pitch: 0,25 A, 0,25 B
 Pin length (detail): 41,3 ± 0,3
 Pin height: 5,4
 Pin diameter: 0,9 ± 0,2
 Pin spacing: 6 ± 0,3
 Pin length (detail): 10,8 ± 0,3
 Pin diameter: 2,84

SOLDER BUCKET FOR AWG 20

SPECIFICATION

Performance level	PL2
Filter type	C
Capacitance	47pf±20%
Working Voltage	100v
Current Rating	7.5A
Insulation Resistance	>1GΩ

FREQUENCY (MHz)	ATTENUATION (dB)
5	-
10	-
50	-
100	-
500	30dB
1000	35dB

			Dat.	Name	 <small>All Dim. in mm Orig. Size DIN A 4</small>	D-Sub, male, straight, 25 Poles, with turned solder bucket and hole	Me?/Stab/ Scale	1.5:1	
			Detail.	CV					
			Insp.	JB					
36283	12/01/12	SD	Stand.						
31897	17/05/04	AF	HARTING EURL F-95972 Paris				Blatt/ Page	TB 09643217210 1/1	
31058	8-JUL-02	CV	Mod.	Dat.	Name	Sub.			