

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190080013

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190080013 - Connector Quick Connect Receptacle 18-22 AWG 0.250" (6.35mm) Crimp



Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## This document was generated on 06/10/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION Part Number: 0190080013 Status: Active **Overview:** Standard Quick-Disconnect Terminals Flag Krimptite<sup>™</sup> Quick Disconnect, Female, for 18-22 (0.80-0.35mm<sup>2</sup>) Wire, Metal **Description:** Strip, Tab 6.35 x 0.81mm **Documents:** Packaging Specification PK-19009-001 (PDF) 3D Model Drawing (PDF) RoHS Certificate of Compliance (PDF) Product Specification PS-19902-011 (PDF) Series image - Reference only Agency Certification LR18689 CSA EU ELV Not Relevant UL E79133 General EU RoHS China RoHS Product Family **Quick Disconnects** Compliant REACH SVHC Series 19008 Crimp Quality Equipment Not Contained Per Yes Insulated No -ED/79/2015 (17 Overview Standard Quick-Disconnect Terminals December 2015) Product Name Krimptite™ Halogen-Free Quick Disconnect Type Status UPC 800755046564 Low-Halogen Need more information on product Physical environmental compliance? Barrel Type Closed Gender Female Email productcompliance@molex.com Glow-Wire Compliant No Please visit the Contact Us section for any Insulation None non-product compliance questions. Lock to Mating Part None China ROHS Green Image Material - Metal Brass Material - Plating Mating ELV Not Relevant Tin Material - Plating Termination Tin 0.620/g Net Weight Orientation Flag Search Parts in this Series Packaging Type Reel 19008 Series Polarized to Mating Part No Tab Thickness 0.81mm Application Tooling | FAQ Tab Width 6.35mm Tooling specifications and manuals are Temperature Range - Operating Per Wire Specification found by selecting the products below. Termination Interface: Style Crimp or Compression Crimp Height Specifications are then Wire Size AWG 18, 20, 22 contained in the Application Tooling Specification document. Electrical Voltage - Maximum Per Wire Specification Global Description Product # Material Info ASP Perishable 0190290130 AAZ-1158 Old Part Number Tool Kit used in ASP presses that process **Reference - Drawing Numbers** metal strip product Packaging Specification PK-19009-001 Mini-Mac<sup>™</sup> 0638027500 **Product Specification** PS-19902-011 Applicator Rear Feed Sales Drawing SD-19008-013

This document was generated on 06/10/2016



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190080013 - Connector Quick Connect Receptacle 18-22 AWG 0.250" (6.35mm) Crimp

PLEASE CHECK WWW MOLEX COM FOR LATEST PART INFORMATION