

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190180047

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190180047 - Connector Quick Connect Receptacle 24-26 AWG 0.187" (4.75mm) Crimp

one company > a world of innovation

<u>Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com</u>

art Number:			
	0190180047		
tatus:	Active		
verview:	Standard Quick-Disconne	<u>ct Terminals</u>	
escription:	/ibraKrimp™ Quick Disco	nnect, Female, for 24-26 (0.20-0.12mm <sup>2</sup> ) Wire, Mylar Tape,	
	Гаb 4.75 х 0.51mm		
Documents:			
Drawing (PDF)		Product Specification PS-19902-015 (PDF)	
Product Specification PS		RoHS Certificate of Compliance (PDF)	
Product Specification PS		KOHS Certificate of Compliance (FDF)	
Product Specification Pa	<u>5-19902-011 (PDF)</u>		Series image - Reference only
			Series image - Reference only
General			
Product Family		Quick Disconnects	EUELV
Series		<u>19018</u>	Not Relevant
Comments		Butted Seam	
Crimp Quality Equipmen	ıt	Yes	EU RoHS China RoHS
Insulated		No	Compliant
Overview		Standard Quick-Disconnect Terminals	REACH SVHC
Product Name		VibraKrimp™	Not Contained Per
Туре		Quick Disconnect	-ED/79/2015 (17
UPC		800753037571	December 2015)
510		000100031011	Halogen-Free
Physical			Status
Barrel Type		Closed	Low-Halogen
Gender		Female	Need more information on product
Glow-Wire Compliant		No	environmental compliance?
Insulation		None	environmental compliance?
Lock to Mating Part		None	Email productcompliance@molex.com
Material - Metal		Brass	Please visit the <u>Contact Us</u> section for any
Material - Plating Mating			non-product compliance questions.
		Tin	non-product compliance questions.
Material - Plating Termin	nation	Tin	China ROHS Green Image
Net Weight		0.452/g	ELV Not Relevant
Orientation		Straight	
Packaging Type		Adhesive Tape on Reel	
Polarized to Mating Part		No	
Tab Thickness		0.51mm	Search Parts in this Series
Tab Width		4.75mm	<u>19018</u> Series
Temperature Range - O		Per Wire Specification	
Wire Insulation Diamete	r	1.00-2.40mm max.	Application Tooling   FAQ
Wire Size AWG		24, 26	Tooling specifications and manuals are
			found by selecting the products below.
Electrical			Crimp Height Specifications are then
Voltage - Maximum		Per Wire Specification	contained in the Application Tooling
O al dan Daa D			Specification document.
Solder Process Data		N1/A	
Lead-freeProcess Capa	ollity	N/A	Global
Matarial Info			Description Product #
Material Info		M 4170T	Mini-Mac <sup>™</sup> <u>0638851700</u>
Old Part Number		M-4172T	Applicator
Reference - Drawing N	umbers		ASP Perishable 0190270181
Product Specification	41110613	PS-19902-005, PS-19902-011, PS-19902-015	Tool Kit used in ASP
			presses that process
Sales Drawing		SD-19018-001	product on tape



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190180047 - Connector Quick Connect Receptacle 24-26 AWG 0.187" (4.75mm) Crimp

PLEASE CHECK WWW MOLEX COM FOR LATEST PART INFORMATION