



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited**  
Datasheet of 0190030097 - Connector Quick Connect Receptacle 18-22 AWG 0.110"  
(2.79mm) Crimp

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Molex Connector Corporation](#)  
[0190030097](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

This document was generated on 03/02/2016

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0190030097](#)  
**Status:** **Active**  
**Overview:** [Standard Quick-Disconnect Terminals](#)  
**Description:** InsulKrimp™ Female Quick Disconnect, for 18-22 AWG Wire Range

**Documents:**

- [3D Model](#) [Product Specification PS-19902-011 \(PDF\)](#)
- [Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
- [Product Specification PS-19902-008 \(PDF\)](#)

**Agency Certification**

CSA LR18689  
 UL E79133

**General**

Product Family Quick Disconnects  
 Series 19003  
 Comments Funnel Entry  
 Crimp Quality Equipment Yes  
 Insulated Fully  
 Overview [Standard Quick-Disconnect Terminals](#)  
 Product Name InsulKrimp™  
 Type Quick Disconnect  
 UPC 800753128859

**Physical**

Barrel Type Closed  
 Color - Resin Red  
 Flammability 94V-2  
 Gender Female  
 Glow-Wire Compliant Yes  
 Insulation Nylon (PA)  
 Lock to Mating Part None  
 Material - Metal Brass  
 Material - Plating Mating Tin  
 Material - Plating Termination Tin  
 Material - Resin Nylon  
 Net Weight 0.462g  
 Orientation Straight  
 Packaging Type Reel  
 Plating min - Mating 4.064µm  
 Plating min - Termination 4.064µm  
 Polarized to Mating Part No  
 Tab Thickness 0.51mm  
 Tab Width 2.79mm  
 Temperature Range - Operating -65°C to +105°C  
 Termination Interface: Style Crimp or Compression  
 Wire Insulation Diameter 3.43mm max.  
 Wire Size AWG 18, 20, 22

**Electrical**


Voltage - Maximum 600V

**Solder Process Data**

Lead-freeProcess Capability N/A

**Material Info**

Old Part Number AA-2204C



**EU ELV**

Not Relevant

**EU RoHS**

Compliant

**China RoHS**

**REACH SVHC**

Not Contained Per  
 -ED/79/2015 (17  
 December 2015)

**Halogen-Free**

Status

**Low-Halogen**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

**Search Parts in this Series**

19003 Series

**Application Tooling | FAQ**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

Description	Product #
Mini-Mac™	0638837000
Applicator	
ASP Perishable	0190280104
Tool Kit used in ASP presses that process continuous molded product	



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited**  
Datasheet of 0190030097 - Connector Quick Connect Receptacle 18-22 AWG 0.110"  
(2.79mm) Crimp

**Reference - Drawing Numbers** [Contact us: sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) [Website: www.integrated-circuit.com](http://www.integrated-circuit.com)

Product Specification  
Sales Drawing

PS-19902-008, PS-19902-011  
SD-19003-005

This document was generated on 03/02/2016

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**