

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190030015

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030015 - Connector Quick Connect Receptacle 18-22 AWG 0.187" (4.75mm) Crimp

one company > a world of innovation

<u>Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com</u>

Part Number:	<u>0190030015</u>			
Status:	Active			The to
Overview: Description:		<u>Standard Quick-Disconnect Terminals</u> InsulKrimp [™] Quick Disconnect, Female, for 18-22 (0.80-0.35mm²), Continuous Molded Strip, Tab 4.75 x 0.51mm		FUNNEL ENTRY BERRATIONS STRESS RELIEVED BARREL
Documents:				WIRE STOP
3D Model		Product Specification PS-19902-011 (PDF)		MOLDED NYLON INSULATED HOUSING
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	- INSULATED HOUSING	
Product Specificati	on PS-19902-008 (PDF)		Series ima	ge - Reference only
Agency Certificat	ion			
CSA		LR18689	EU ELV	
UL		E79133	Not Relevant	
General			EU RoHS	China RoHS
Product Family		Quick Disconnects	Compliant	
Series		<u>19003</u>	REACH SVHC	
Comments		Funnel Entry	Not Contained Pe	r -
Crimp Quality Equipment		Yes	ED/108/2014 (17 I	Dec
Insulated		Fully	2014)	
Overview		Standard Quick-Disconnect Terminals	Halogen-Free	
Product Name		InsulKrimp™	Status	
Туре		Quick Disconnect	Low-Halogen	
UPC		800753028562	Need more inform environmental co	nation on product
Physical				•
Barrel Type		Closed		pliance@molex.com
Color - Resin		Red		ontact Us section for any
Flammability		94V-2	non-product comp	liance questions.
Gender	ant .	Female	China ROHS	Green Image
Glow-Wire Complia	ant	Yes Nules (DA)	ELV	Not Relevant
Insulation Lock to Mating Par	t	Nylon (PA) None		
Material - Metal	L	Brass		
Material - Plating Mating		Tin		
Material - Plating Mating Material - Plating Termination		Tin	Search Parts in this Series	
Material - Resin		Nylon	<u>19003</u> Series	
Net Weight		0.838/g		
Orientation		Straight	Application To	
Packaging Type		Reel		ations and manuals are
Plating min - Matin	q	4.064µm		ng the products below.
Plating min - Termi		4.064µm		pecifications are then
Polarized to Mating		No		Application Tooling
Tab Thickness		0.51mm	Specification do	cument.
Tab Width		4.75mm	Global	Draduct #
Temperature Rang	e - Operating	-65°C to +105°C	Description	Product #
Termination Interfa	,	Crimp or Compression	Mini-Mac™	0638837200
Wire Insulation Dia	meter	5.84mm max.	Applicator	
Wire Size AWG		18, 20, 22		
Electrical				
Voltage - Maximun	1	600V		
Solder Process D				
Lead-freeProcess	Japability	N/A		

Material Info



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030015 - Connector Quick Connect Receptacle 18-22 AWG 0.187" (4.75mm) Crimp

Old Part Number

er Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Reference - Drawing Numbers Product Specification Sales Drawing

PS-19902-008, PS-19902-011 SD-19003-006

This document was generated on 03/03/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION