

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190180025

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190180025 - Connector Quick Connect Receptacle 12-14 AWG 0.250" (6.35mm) Crimp



Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 03/07/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION Part Number: 0190180025 Status: Active Standard Quick-Disconnect Terminals **Overview: Description:** VibraKrimp[™] Quick Disconnect, Female, for 12-14 (3.30-2.00mm²) Wire, Mylar Tape, Tab 6.35 x 0.81mm **Documents:** Drawing (PDF) Product Specification PS-19902-015 (PDF) Product Specification PS-19902-005 (PDF) RoHS Certificate of Compliance (PDF) Product Specification PS-19902-011 (PDF) Series image - Reference only Agency Certification LR18689 CSA EU ELV UL E79133 Not Relevant General EU RoHS China RoHS **Product Family Quick Disconnects** Compliant REACH SVHC Series 19018 Butted Seam Not Contained Per Comments Crimp Quality Equipment -ED/79/2015 (17 Yes Insulated No December 2015) Overview Standard Quick-Disconnect Terminals Halogen-Free VibraKrimp™ Product Name Status Type UPC Quick Disconnect Low-Halogen 800753037489 Need more information on product environmental compliance? Physical Barrel Type Closed Email productcompliance@molex.com Female Gender Please visit the Contact Us section for any **Glow-Wire Compliant** No non-product compliance questions. Insulation None China ROHS Green Image Lock to Mating Part None Material - Metal Brass ELV Not Relevant Material - Plating Mating Tin Material - Plating Termination Tin Net Weight 0.792/g Search Parts in this Series Orientation Straight 19018 Series Packaging Type Adhesive Tape on Reel Polarized to Mating Part No Application Tooling | FAQ Tab Thickness 0.81mm Tooling specifications and manuals are Tab Width 6.35mm found by selecting the products below. Temperature Range - Operating Per Wire Specification Crimp Height Specifications are then Wire Insulation Diameter 2.50-4.40mm contained in the Application Tooling Wire Size AWG 12.14 Specification document. Electrical Global Voltage - Maximum Per Wire Specification Description Product # ATP Crimp Dies 0190270187 Material Info for the Tape Crimp Old Part Number P-4178T Module and ATP-101 & 301 Press **Reference - Drawing Numbers** PS-19902-005, PS-19902-011, PS-19902-015 Product Specification Sales Drawing 19018001

This document was generated on 03/07/2016



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190180025 - Connector Quick Connect Receptacle 12-14 AWG 0.250" (6.35mm) Crimp

PLEASE CHECK WWW MOLEX COM FOR LATEST PART INFORMATION