

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190030014

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030014 - Connector Quick Connect Receptacle 18-22 AWG 0.187" (4.75mm) Crimp

one company > a world of innovation

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 03/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION Part Number: 0190030014 Status: Active Standard Quick-Disconnect Terminals **Overview: Description:** InsulKrimp[™] Quick Disconnect, Female, for 18-22 (0.80-0.35mm²), Box, Tab 4.75 x 0.51mm **Documents:** Product Specification PS-19902-011 (PDF) 3D Model MOLDED NYLON INSULATED HOUSING Drawing (PDF) RoHS Certificate of Compliance (PDF) Product Specification PS-19902-008 (PDF) Series image - Reference only **Agency Certification** LR18689 CSA EU ELV UL E79133 Not Relevant General EU RoHS China RoHS **Product Family Quick Disconnects** Compliant REACH SVHC Series 19003 Funnel Entry Not Contained Per -Comments Crimp Quality Equipment Yes ED/108/2014 (17 Dec Insulated Fullv 2014) Overview Standard Quick-Disconnect Terminals Halogen-Free InsulKrimp™ Product Name Status Type UPC Quick Disconnect Low-Halogen 800753028555 Need more information on product environmental compliance? Physical Barrel Type Closed Email productcompliance@molex.com Color - Resin Red Please visit the Contact Us section for any 94V-2 Flammability non-product compliance questions. Gender Female China ROHS Green Image **Glow-Wire Compliant** Yes Insulation Nylon (PA) ELV Not Relevant Lock to Mating Part None Material - Metal Brass Material - Plating Mating Tin Search Parts in this Series Material - Plating Termination Tin 19003 Series Material - Resin Nvlon Net Weight 0.787/q Application Tooling | FAQ Orientation Straight Tooling specifications and manuals are Packaging Type Bag found by selecting the products below. Plating min - Mating 4.064µm Crimp Height Specifications are then Plating min - Termination Polarized to Mating Part 4.064µm contained in the Application Tooling No Specification document. Tab Thickness 0.51mm Global Tab Width 4.75mm Description Product # Temperature Range - Operating -65°C to +105°C Hand Crimp Tool 0640010400 Termination Interface: Style Crimp or Compression Crimp Head for the 0640050400 Wire Insulation Diameter 5.84mm max. AT-200[™] Pneumatic Wire Size AWG 18, 20, 22 Hand Tool Electrical 600V Voltage - Maximum Solder Process Data Lead-freeProcess Capability N/A

Material Info



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030014 - Connector Quick Connect Receptacle 18-22 AWG 0.187" (4.75mm) Crimp

Old Part Number

er Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Reference - Drawing Numbers Product Specification Sales Drawing

PS-19902-008, PS-19902-011 SD-19003-006

This document was generated on 03/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION