

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190030068

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



one company > a world of innovation

**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190030068 - Connector Quick Connect Receptacle 24-26 AWG 0.187" (4.75mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Part Number:	<u>0190030068</u>		
			*.
	Active		A By A
escription:	<u>Standard Quick-Diso</u> InsulKrimp™ Quick 0.81mm	<u>connect Terminals</u> Disconnect, Female, for 24-26 (0.20-0.12mm²), Box, Tab 4.75 x	
-			- E DEEP WIRE GRIP SERRATIONS SERRATIONS SERRATIONS SERRATIONS SERRATIONS SERRATIONS SERRATIONS
Documents:			STOP
<u>3D Model</u>		RoHS Certificate of Compliance (PDF)	
Drawing (PDF)			Insochieb Hoosing
General			Series image - Reference only
Product Family		Quick Disconnects	
Series		<u>19003</u>	EU ELV
Comments		Funnel Entry	Not Relevant
Crimp Quality Equipment	nt	Yes	
Insulated		Fully	EU RoHS China RoHS
Overview		Standard Quick-Disconnect Terminals	Compliant
Product Name		InsulKrimp™	REACH SVHC
Туре		Quick Disconnect	Not Contained Per
UPC		800754884006	-ED/79/2015 (17
010		00010-000	December 2015)
Physical			Halogen-Free
Barrel Type		Closed	Status
Color - Resin		Yellow	Not Low-Halogen
Gender		Female	Need more information on product
Glow-Wire Compliant		Yes	environmental compliance?
Insulation		Nylon (PA)	environmental compliance.
Lock to Mating Part		None	Email productcompliance@molex.com
Material - Metal		Brass	Please visit the Contact Us section for any
Material - Plating Mating	r	Tin	non-product compliance questions.
Material - Plating Termi		Tin	····· F
Material - Resin	nation	Nylon	China ROHS Green Image
Net Weight		0.726/g	ELV Not Relevant
Orientation		Straight	,
Packaging Type		-	
		Bag	Search Parts in this Series
Plating min - Mating		4.064µm	
Plating min - Terminatio		4.064µm	<u>19003</u> Series
Polarized to Mating Par	t	No 0.81mm	
Tab Thickness		0.81mm	Application Tooling   FAQ
Tab Width		4.75mm	Tooling specifications and manuals are
Temperature Range - C		-65°C to +105°C	found by selecting the products below.
Termination Interface: S		Crimp or Compression	Crimp Height Specifications are then
Wire Insulation Diameter	er	1.90mm max.	contained in the Application Tooling
Wire Size AWG		24, 26	Specification document.
Electrical		coo)/	Global Description Product #
Voltage - Maximum		600V	Hand Crimp Tool 0640015200
Solder Process Data			Crimp Head for the 0640055200
Lead-freeProcess Capa	bility	N/A	AT-200™ Pneumatic
Material Info			Hand Tool
Old Part Number		M-2211	
Reference - Drawing N	lumbers		
Sales Drawing		SD-19003-005	



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190030068 - Connector Quick Connect Receptacle 24-26 AWG 0.187" (4.75mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 07/01/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION