

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190030111

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030111 - Connector Quick Connect Receptacle 18-22 AWG 0.250" (6.35mm) Crimp

one company > a world of innovation

<u>Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com</u>

This document was generated on 03/04/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION Part Number: 0190030111 Status: Active в =Ħ **Overview:** Standard Quick-Disconnect Terminals = = = = = **Description:** InsulKrimp™ Quick Disconnect, Female, Continuous Molded Strip, Tab 6.35 x 0.81mm **Documents:** t Drawing (PDF) Product Specification PS-19902-011 (PDF) D Ε Product Specification PS-19902-008 (PDF) RoHS Certificate of Compliance (PDF) ī ŧ Α Agency Certification Series image - Reference only E79133 General EU ELV Product Family Quick Disconnects Not Relevant 19003 Series Comments Funnel Entry EU RoHS China RoHS Crimp Quality Equipment Yes Compliant REACH SVHC Insulated Fully Overview Standard Quick-Disconnect Terminals Not Contained Per InsulKrimp™ Product Name -ED/79/2015 (17 Quick Disconnect Туре December 2015) UPC 800753129085 Halogen-Free Status Physical Not Low-Halogen Barrel Type Closed Need more information on product Color - Resin Red environmental compliance? Flammability 94V-0 Gender Female Email productcompliance@molex.com Glow-Wire Compliant Yes Please visit the Contact Us section for any Nylon (PA) Insulation non-product compliance questions. Lock to Mating Part None China ROHS Green Image Material - Metal Brass Material - Plating Mating ELV Not Relevant Tin Material - Plating Termination Tin Material - Resin Nylon Net Weight 0.951/g Search Parts in this Series Orientation Straight 19003 Series Packaging Type Reel 4.064µm Plating min - Mating Application Tooling | FAQ Plating min - Termination 4.064µm Tooling specifications and manuals are Polarized to Mating Part No found by selecting the products below. Tab Thickness 0.81mm Crimp Height Specifications are then Tab Width 6.35mm contained in the Application Tooling Temperature Range - Operating -65°C to +105°C Specification document. Termination Interface: Style Crimp or Compression Global Wire Size AWG 18, 20, 22 Description Product # Mini-Mac™ 0638837000 Electrical Applicator Voltage - Maximum 600V ASP Perishable 0190280104 Solder Process Data Tool Kit used in ASP N/A Lead-freeProcess Capability presses that process continuous molded Material Info product Old Part Number AA-2201VNC **Reference - Drawing Numbers** PS-19902-008, PS-19902-011 **Product Specification**



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030111 - Connector Quick Connect Receptacle 18-22 AWG 0.250" (6.35mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 03/04/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION