

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190190015

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190190015 - Connector Quick Connect Receptacle 18-22 AWG 0.205" (5.21mm) Crimp

one company > a world of innovation

<u>Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com</u>

This document was generated on 03/07/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION			
Part Number:	0190190015		
Status:	Active		-W-
<b>O</b>			12-7
Overview: Standard Quick-Disconnect Terminals   Description: Avikrimp™ Quick Disconnect, Female, for 18-22 (0.80-0.35mm²) Wire, Box, T			
Description:	0.81mm	nect, Female, for 18-22 (0.80-0.35mm-) wire, Box, Tab 5.21	× G
Documents:			
Drawing (PDF)		Product Specification PS-19902-014 (PDF)	
	PS-19902-011 (PDF)	RoHS Certificate of Compliance (PDF)	
Product Specification PS-19902-013 (PDF)			Series image - Reference only
General			
Product Family		Quick Disconnects	EUELV
Series		<u>19019</u>	Not Relevant
Crimp Quality Equipn	nent	Yes	EU RoHS China RoHS
Insulated		Partial	
Overview		Standard Quick-Disconnect Terminals	
Product Name		Avikrimp™	REACH SVHC
Туре		Quick Disconnect	Not Contained Per
UPC		800753037984	-ED/79/2015 (17
Dhysical			December 2015)
Physical Barrel Type		Closed	<u>Halogen-Free</u> Status
Color - Resin		Red	
Gender		Female	Not Low-Halogen
Glow-Wire Compliant		No	Need more information on product
Insulation	L	Nylon (PA)	environmental compliance?
Lock to Mating Part		None	Email productcompliance@molex.com
Material - Metal		Brass	Please visit the Contact Us section for any
Material - Plating Mating		Tin	non-product compliance questions.
Material - Plating Termination		Tin	
Net Weight		0.731/g	China ROHS Not Relevant
Orientation		Straight	ELV Not Relevant
Packaging Type		Bag	,
Polarized to Mating P	Part	No	
Tab Thickness		0.81mm	Search Parts in this Series
Tab Width		5.21mm	<u>19019</u> Series
Temperature Range	- Operating	-65°C to +105°C	
Wire Insulation Diam		2.90mm max.	
Wire Size AWG		18, 20, 22	Application Tooling FAQ   Tooling specifications and manuals are
Electrical			found by selecting the products below.
Voltage - Maximum		300V	Crimp Height Specifications are then contained in the Application Tooling
Material Info			Specification document.
Old Part Number		AA-8190-032	Global
<b>.</b>			Description Product #
Reference - Drawing			PremiumGrade™ <u>0640010200</u>
Product Specification	1	PS-19902-011, PS-19902-013, PS-19902-014	Hand Crimp Tool
Sales Drawing		AACD80501, SD-19019-001	Crimp Head for the 0640050200
			AT-200 <sup>™</sup> Pneumatic
			Hand Tool

This document was generated on 03/07/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION