

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190030136

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030136 - Connector Quick Connect Receptacle 14-16 AWG 0.187" (4.75mm) Crimp



UL

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 03/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION Part Number: 0190030136 Status: Active в Standard Quick-Disconnect Terminals **Overview: Description:** InsulKrimp[™] Quick Disconnect, Female, Mylar Tape, Tab 4.75 x 0.81mm **Documents:** Drawing (PDF) Product Specification PS-19902-015 (PDF) Е Product Specification PS-19902-008 (PDF) RoHS Certificate of Compliance (PDF) Product Specification PS-19902-011 (PDF) А Series image - Reference only **Agency Certification** E79133 EU ELV General Not Relevant Quick Disconnects **Product Family** Series <u>19003</u> EU RoHS China RoHS Comments Funnel Entry Not Reviewed REACH SVHC Crimp Quality Equipment Yes Insulated Fully Not Reviewed Standard Quick-Disconnect Terminals Overview Halogen-Free Product Name InsulKrimp™ Status **Quick Disconnect** Туре Not Reviewed UPC 800756386911 Need more information on product environmental compliance? Physical Barrel Type Closed Email productcompliance@molex.com Color - Resin Blue Please visit the Contact Us section for any Flammability 94V-0 non-product compliance questions. Female Gender China ROHS Not Reviewed **Glow-Wire Compliant** Yes ELV Not Relevant Insulation Nylon (PA) Lock to Mating Part None Material - Metal Brass Material - Plating Mating Tin Search Parts in this Series Material - Plating Termination Tin 19003 Series Material - Resin Nylon Net Weight 0.760/g Application Tooling | FAQ Orientation Straight Tooling specifications and manuals are Adhesive Tape on Reel Packaging Type found by selecting the products below. Plating min - Mating 4.064µm Crimp Height Specifications are then Plating min - Termination 4.064µm contained in the Application Tooling Polarized to Mating Part No Specification document. Tab Thickness 0.81mm Global Tab Width 4.75mm Description Product # Temperature Range - Operating -65°C to +105°C Mini-Mac™ 0638854200 Termination Interface: Style Crimp or Compression Applicator Wire Size AWG 14, 16 Electrical Voltage - Maximum 600V

Material Info Old Part Number

Reference - Drawing Numbers Product Specification Sales Drawing

PS-19902-008, PS-19902-011, PS-19902-015 SD-19003-002

BB-2208VT



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030136 - Connector Quick Connect Receptacle 14-16 AWG 0.187" (4.75mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 03/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION