

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0191640052

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0191640052 - NYL. SNAP PLUG REC. PERMA-SEAL Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

X 0 one company > a world of innovation

This document was generated on 03/04/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION			
Part Number:			
	<u>0191640052</u>		
Status:	Active		
Overview:	Snap Plugs and Recepta	icles	
Description: Perma-Seal [™] Snap P		g Receptacle for 18-22 AWG Wire, Diameter 3.96mm	
_			—
Documents:			
Drawing (PDF)		Product Specification PS-19902-013 (PDF)	
Product Specification	PS-19902-011 (PDF)	RoHS Certificate of Compliance (PDF)	
Agency Certification	ı		
UL		E152602	Series image - Reference only
0			
General Draduat Familia		Quick Disconnecto	<u>EU ELV</u>
Product Family		Quick Disconnects	Not Relevant
Series		<u>19164</u>	
Crimp Quality Equipm	ient	Yes	EU RoHS China RoHS
Insulated		Fully	Not Reviewed
Overview		Snap Plugs and Receptacles	REACH SVHC
Product Name		Perma-Seal™	Not Reviewed
Туре		Snap Receptacle	Halogen-Free
UPC		800753113374	Status
Physical			Not Reviewed
Barrel Type		Closed	Need more information on product
Color - Resin		Red	environmental compliance?
Gender			
		Female	Email productcompliance@molex.com
Glow-Wire Compliant Insulation		No	Please visit the <u>Contact Us</u> section for any
		NiAc™	non-product compliance questions.
Lock to Mating Part		None	China ROHS Not Relevant
Material - Metal		Brass	ELV Not Relevant
Material - Plating Mating		Tin	
Material - Plating Terr	mination	Tin	
Material - Resin		Nylon	
Net Weight		1.179/g	Search Parts in this Series
Orientation		Straight	<u>19164</u> Series
Packaging Type		Bag	
Plating min - Mating		4.064µm	Application Tooling FAQ
Plating min - Termina	ition	4.064µm	Tooling specifications and manuals are
Tab Thickness		N/A	found by selecting the products below.
Tab Width		N/A	Crimp Height Specifications are then
Temperature Range - Operating		-55°C to +125°C	contained in the Application Tooling
Termination Interface	5	Crimp or Compression	Specification document.
Wire Insulation Diame	eter	3.30mm max.	Global
Wire Size AWG		18, 20, 22	Description Product #
Electrical			Crimp Head for the 0640054700
		600)/	AT-200 [™] Pneumatic
Voltage - Maximum		600V	Hand Tool
Material Info			
Old Part Number		SBRA-8156N	Hand Crimp Tool 0640014700
Reference - Drawing	y Numbers		
Product Specification		PS-19902-011, PS-19902-013	
Sales Drawing		SD-19164-035	

This document was generated on 03/04/2016



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0191640052 - NYL. SNAP PLUG REC. PERMA-SEAL Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION