

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0192030390

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



molex[®]

Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0192030390 - Connector Quick Connect Receptacle 14-16 AWG 0.250" (6.35mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

	innovation	This demonstrations and the contract of the OO/OO/OOAO		
This document was generated on 03/03/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION				
Part Number:	0192030390			
Status:	Active			4 0
			-	.00
overview: Description:	<u>Standard Quick-Disconnect Terminals</u> Krimptite™ Quick Disconnect, Female Steel 900 Degree F/383 Degree C, 14-16 AWG, Tab 6.35mm		80	
Documents: Drawing (PDF) Product Specificatio	on PS-19902-011 (PDF)	Product Specification PS-19902-013 (PDF) RoHS Certificate of Compliance (PDF)		and and a
General			Series ima	ge - Reference only
Product Family		Quick Disconnects		
Series		19203	EU ELV	
	mont	<u>19205</u> Yes	Not Relevant	
Crimp Quality Equip	JITEIL	Yes No	Not Relevant	
			EU RoHS	China RoHS
Overview		Standard Quick-Disconnect Terminals	Compliant	
Product Name		Krimptite™	REACH SVHC	
Туре		Quick Disconnect	Not Contained Pe	r
UPC		822348428175	-ED/79/2015 (17	
Dhysical			December 2015)	
Physical		Olarad	Halogen-Free	
Barrel Type		Closed	Status	
Gender		Male		
Glow-Wire Compliant		No	Low-Halogen	
Insulation		None		nation on product
Lock to Mating Part		None	environmental co	ompliance?
Material - Metal		Steel	Empil productoom	nlianaa @malay aam
Material - Plating Mating		Nickel	Email <u>productcompliance@molex.com</u> Please visit the <u>Contact Us</u> section for any	
Material - Plating Termination		Nickel		
Net Weight		0.601/g	non-product comp	liance questions.
Orientation		Straight	China ROHS	Green Image
Packaging Type		Bag	ELV	Not Relevant
Tab Thickness		0.80mm		NOLINGIEVAIIL
Tab Width		7.70mm		
Temperature Range	e - Operating	-65°C to +105°C		
Wire Size AWG		14, 16	Search Parts in	this Series
			19203 Series	
Electrical				
Voltage - Maximum		N/A	Application To	
Material Info				ations and manuals are ng the products below.
Reference - Drawir	ng Numbors			pecifications are then
		DS 10002 011 DS 10002 012		Application Tooling
Product Specificatio)[]]	PS-19902-011, PS-19902-013		
Sales Drawing		SD-19203-025	Specification do	cument.
			Global	Dural 61
			Description	Product #
			Hand Crimp Too	
				the 0640071100
			AT-200™ Pneu	matic
			Hand Tool	

This document was generated on 03/03/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION