

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Mallory Sonalert Products](#)  
[PLD-21N30WQ](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

|   |                           |
|---|---------------------------|
| <b>MALLORY</b> Mallory Sonalert Products Inc. | Part # <b>PLD-21N30WQ</b> |
| <b>Sales Outline Drawing</b>                  | Revision <b>A</b>         |

**Specifications:**

|                                  |   |
|----------------------------------|---|
| Oscillation Frequency (Hz)       | 3000 ± 500                                      |
| Operating Voltage (Vdc)          | 3 ~ 30  |
| Rated Voltage (Vdc)              | 12  |
| Current Consumption (mA/max)     | 12 at Rated Voltage                             |
| Sound Pressure Level (dB/min)    | 80 at 30cm at Rated voltage                     |
| Tone/Pulse Rate (Hz0)            | Constant + Slow Pulse 1.2 ±20%                  |
| Operating Temperature (°C)       | -20 ~ +70                                       |
| Storage Temperature (°C)         | -30 ~ +80                                       |
| Housing                          | ABS 777D UL94HB plastic resin<br>(Color: Black) |
| Lead Wire                        | 28 AWG  |
| Weight (Grams)                   | 3.2   |
| Condition by wave soldering (°C) | 245 ±5 / 3±0.5 sec                              |
| Condition by hand soldering (°C) | 350 ±20 / within 5 sec                          |
| Options                          | For other options contact factory               |

**RoHS Compliant**

**Dimensions:** (units: mm)

