

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0467070001

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0467070001 - 4P15S TEN50 HARNESS CONN HOUSING Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

molex[®] one company > a world of innovation

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION			
Part Number:	0467070001		
	Active		
		TM High-Current Connector	
	EXTreme Ten60Power [™] High-Current Connector 2.54mm, 7.50mm Pitch EXTreme Ten60Power [™] Receptacle Housing, 15 Signal		
	Circuits, 4 Power Circuits, Halogen-Free		
Documents:			
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
Agency Certification			0
CSA		LR19980	Series image - Reference only
UL		E29179	
Comorel			EU ELV
General Product Family		Crimp Housings	Not Relevant
Series		46707	EU RoHS China RoHS
Application		Power, Signal, Wire-to-Wire	Compliant
Comments		Used with <u>467090005</u> Signal housings & <u>467080001</u>	REACH SVHC
		TPA	Not Contained Per
Overview		EXTreme Ten60Power™ High-Current Connector	-ED/79/2015 (17
Product Name		EXTreme Ten60Power™	December 2015)
UPC		883906132873	Halogen-Free
Dhusiaal			Status
Physical Circuits (maximum)		19	Low-Halogen
Circuits Detail		19	Need more information on product
Color - Resin		Black	environmental compliance?
Flammability		94V-0	Email productcompliance@molex.com
Gender		Receptacle	Please visit the <u>Contact Us</u> section for any
Glow-Wire Compliant		No	non-product compliance questions.
Keying to Mating Part		None	
Lock to Mating Part		Yes	China ROHS Green Image
Material - Resin		Nylon	ELV Not Relevant
Net Weight		8.857/g	
Number of Rows		1	
Packaging Type		Tray	Search Parts in this Series
Panel Mount		No	<u>46707</u> Series
Pitch - Mating Interface Polarized to Mating Par		2.54mm, 7.50mm Yes	
Stackable	L	No	Mates With
Temperature Range - C	Derating	-40°C to +105°C	<u>46437-1023</u> EXTreme Ten60Power™ Righ
			Angle Plug Assembly
Solder Process Data			
Lead-freeProcess Capa	ability	N/A	Use With
Material Info			44262 Crimp Terminal Receptacles, <u>70058</u> SL [™] Crimp Terminal
Reference - Drawing	lumbers		· ·
Sales Drawing		SD-46707-001	

This document was generated on 03/02/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION