

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151660533

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



one company > a world of innovation

Status:AOverview:PDescription:0.	305m Cable Length, Cab	pers [™] FFC Jumper, Same Side Contacts (Type A), 46 Circuit ole Thickness 0.12mm, Tin (Sn) Plating <u>Packaging Specification PK-15166-001 (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u> Cable <u>15166</u> Contacts on the same side, Type A	ts, Series image - Reference only
Status: A Overview: P Description: 0. 0. Documents: Drawing (PDF)	Ctive remo-Flex™ Cable Jump 50mm Pitch Premo-Flex™ 305m Cable Length, Cab	[™] FFC Jumper, Same Side Contacts (Type A), 46 Circuits ble Thickness 0.12mm, Tin (Sn) Plating Packaging Specification PK-15166-001 (PDF) RoHS Certificate of Compliance (PDF) Cable 15166	Series image - Reference only
Overview: P Description: 0. 0. Documents: Drawing (PDF)	remo-Flex™ Cable Jump 50mm Pitch Premo-Flex⊺ 305m Cable Length, Cab	[™] FFC Jumper, Same Side Contacts (Type A), 46 Circuits ble Thickness 0.12mm, Tin (Sn) Plating Packaging Specification PK-15166-001 (PDF) RoHS Certificate of Compliance (PDF) Cable 15166	Series image - Reference only
Description: 0. 0. Documents: Drawing (PDF)	50mm Pitch Premo-Flex 305m Cable Length, Cab	[™] FFC Jumper, Same Side Contacts (Type A), 46 Circuits ble Thickness 0.12mm, Tin (Sn) Plating Packaging Specification PK-15166-001 (PDF) RoHS Certificate of Compliance (PDF) Cable 15166	Series image - Reference only
0. Documents: Drawing (PDF)	305m Cable Length, Cab	Dele Thickness 0.12mm, Tin (Sn) Plating Packaging Specification PK-15166-001 (PDF) RoHS Certificate of Compliance (PDF) Cable 15166	Series image - Reference only
Drawing (PDF)	. <u>15166-001 (PDF)</u>	RoHS Certificate of Compliance (PDF) Cable 15166	
	<u>15166-001 (PDF)</u>	RoHS Certificate of Compliance (PDF) Cable 15166	
	<u>15166-001 (PDF)</u>	RoHS Certificate of Compliance (PDF) Cable 15166	
		<u>15166</u>	
General		<u>15166</u>	EU ELV
Product Family			EUELV
Series		Contacts on the same side. Type A	
Comments		Contacts on the same side, Type A	Not Reviewed
Crimp Quality Equipment		Yes	
Overview		Premo-Flex [™] Cable Jumpers	EU RoHS China RoHS
Product Name		Premo-Flex™FFC Jumper	Not Reviewed
UPC		884982850316	REACH SVHC
			Not Reviewed
Physical			Halogen-Free
Cable Length		0.305m	<u>Status</u>
Circuits (Loaded)		48	Not Reviewed
Circuits (maximum)		48	Need more information on product
Net Weight		1.000/g	environmental compliance?
Packaging Type		Bag	
Pitch - Termination Interfa		0.50mm	Email productcompliance@molex.com
Temperature Range - Op	erating	-40°C to +105°C	Please visit the <u>Contact Us</u> section for any
Wire Size AWG		N/A	non-product compliance questions.
Wire/Cable Type		Flat Flex Cable	China ROHS Not Reviewed
Electrical			ELV Not Reviewed
Current - Maximum per C	ontaat	0.5A	1 Let Not Reviewed
Voltage - Maximum per C	Unidu	0.5A 60V AC	
voltage - Maximum		OUV AC	
Material Info			Search Parts in this Series
Reference - Drawing Nu	mbers		
Packaging Specification		PK-15166-001	Use With
Product Specification		PS-15166-001	<a href="www.molex.com/link/ffc-</td></tr><tr><td>Sales Drawing</td><td></td><td>SD-15166-001</td><td>fpc.html">Molex FFC – FPC connector

This document was generated on 03/08/2016

This document was generated on 03/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Be sure to match like plating