

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151670229

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



## molex<sup>®</sup> one company > a world of innovation

|                               | <u>151670229</u><br>ctive                                     |   |   |
|-------------------------------|---|---|---|
|                               | remo-Flex™ Cable Jun  | npers   |   |
|                               |   | x <sup>™</sup> FFC Jumper, Same Side Contacts (Type A), 8 Circuits, |   |
| 0.                            | 0.102m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating |   |   |
| Documents:                    |   |   |   |
| Drawing (PDF)                 |   | Packaging Specification PK-15167-001 (PDF)                          |   |
| Product Specification PS-     | <u>15167-001 (PDF)</u>  | RoHS Certificate of Compliance (PDF)                                |   |
| General                       |   |   | Series image - Reference only   |
| Product Family                |   | Cable   |   |
| Series                        |   | <u>15167</u>  | EU ELV  |
| Comments                      |   | Contacts on the same side, Type A                                   | Not Reviewed  |
| Crimp Quality Equipment       |   | Yes   |   |
| Overview                      |   | Premo-Flex <sup>™</sup> Cable Jumpers                               | EU RoHS China RoHS  |
| Product Name                  |   | Premo-Flex <sup>™</sup> FFC Jumper                                  | Not Reviewed  |
| UPC                           |   | 884982851122  | REACH SVHC  |
| Physical                      |   |   | Not Reviewed  |
| Cable Length                  |   | 0.102m  | Halogen-Free  |
| Circuits (Loaded)             |   | 8   | Status<br>Not Reviewed  |
| Circuits (maximum)            |   | 8   |   |
| Net Weight                    |   | 8<br>1.000/g  | Need more information on product  |
| Packaging Type                |   | Bag   | environmental compliance?   |
| Pitch - Termination Interface |   | 1.00mm  | Email productcompliance@molex.com   |
| Temperature Range - Operating |   | -40°C to +105°C   | Please visit the Contact Us section for any   |
| Wire Size AWG                 |   | N/A   | non-product compliance questions.   |
| Wire/Cable Type               |   | Flat Flex Cable   |   |
|                               |   |   | China ROHS Not Reviewed   |
| Electrical                    |   |   | ELV Not Reviewed  |
| Current - Maximum per C       | ontact  | 1.2A  |   |
| Voltage - Maximum             |   | 60V AC  |   |
| Material Info                 |   |   | Search Parts in this Series   |
| Reference - Drawing Nu        | mbers   |   |   |
| Packaging Specification       |   | PK-15167-001  | Use With  |
| Product Specification         |   | PS-15167-001  | <a href="www.molex.com/link/ffc-&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Sales Drawing&lt;/td&gt;&lt;td&gt;&lt;/td&gt;&lt;td&gt;SD-15167-001&lt;/td&gt;&lt;td&gt;fpc.html">Molex FFC – FPC connector</a> |
|                               |   |   | Be sure to match like plating   |

This document was generated on 03/09/2016

## This document was generated on 03/09/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION