

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151680165

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



molex[®] one company > a world of innovation

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION		
Description: 1.25mm Pite	1165 [™] Cable Jumpers ch Premo-Flex [™] FFC Jumper, Same Side Contacts (Type A), 10 Circuits, ble Length, Cable Thickness 0.12mm, Tin (Sn) Plating	
Documents: Drawing (PDF) Product Specification PS-15168-00	Packaging Specification PK-15168-001 (PDF) 1 (PDF) RoHS Certificate of Compliance (PDF)	
General		Series image - Reference only
Product Family	Cable	
Series	15168	EUELV
Comments	Contacts on the same side, Type A	Not Reviewed
Crimp Quality Equipment	Yes	
Overview	Premo-Flex [™] Cable Jumpers	EU RoHS China RoHS
Product Name	Premo-Flex™FFC Jumper	Not Reviewed
UPC	884982855755	REACH SVHC
		Not Reviewed
Physical		Halogen-Free
Cable Length	0.305m	<u>Status</u>
Circuits (Loaded)	10	Not Reviewed
Circuits (maximum)	10	Need more information on product
Net Weight	1.000/g	environmental compliance?
Packaging Type	Bag	
Pitch - Termination Interface	1.25mm	Email productcompliance@molex.com
Temperature Range - Operating	-40°C to +105°C	Please visit the Contact Us section for any
Wire Size AWG	N/A	non-product compliance questions.
Wire/Cable Type	Flat Flex Cable	China ROHS Not Reviewed
Electrical		ELV Not Reviewed
Current - Maximum per Contact	1.4A	, [
Voltage - Maximum	60V AC	
Material Info		Search Parts in this Series 15168 Series
Reference - Drawing Numbers		
Packaging Specification	PK-15168-001	Use With
Product Specification	PS-15168-001	<a href="www.molex.com/link/ffc-</td></tr><tr><td>Sales Drawing</td><td>SD-15168-001</td><td>fpc.html">Molex FFC – FPC connector<!--</td-->

This document was generated on 03/04/2016

This document was generated on 03/04/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Be sure to match like plating