

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151680202

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



molex[®] one company > a world of innovation

Part Number: 0151680202 Status: Active	
Dverview: Premo-Flex™ Cable Jumpers Description: 1.25mm Pitch Premo-Flex™ FFC Jumper, Opposite Side Contacts (Circuits, 0.178m Cable Length, Cable Thickness 0.12mm, Tin (Sn) F	Plating
Documents: Drawing (PDF) Packaging Specification PK-15168- Product Specification PS-15168-001 (PDF) RoHS Certificate of Compliance (P	
General	Series image - Reference only
Product Family Cable Series 15168	EU ELV
Comments Contacts on opposite sides, Type D	Not Reviewed
Crimp Quality Equipment Yes	Not Keviewed
Overview Premo-Flex [™] Cable Jumpers	EU RoHS China RoHS
Product Name Premo-Flex™FFC Jumper	Not Reviewed
UPC 884982856127	REACH SVHC
	Not Reviewed
Physical	Halogen-Free
Cable Length 0.178m	Status
Circuits (Loaded) 14	Not Reviewed
Circuits (maximum) 14	Need more information on product
Net Weight 1.000/g	environmental compliance?
Packaging Type Bag	
Pitch - Termination Interface 1.25mm	Email productcompliance@molex.com
Temperature Range - Operating -40°C to +105°C	Please visit the Contact Us section for any
Wire Size AWG N/A	non-product compliance questions.
Wire/Cable Type Flat Flex Cable	China ROHS Not Reviewed
Electrical	ELV Not Reviewed
Current - Maximum per Contact 1.4A	
Voltage - Maximum 60V AC	
Material Info	Search Parts in this Series 15168 Series
Reference - Drawing Numbers	
Packaging Specification PK-15168-001	Use With
Product Specification PS-15168-001	<pre>cse with <a href="www.molex.com/link/ffc-</pre></td></tr><tr><td>Sales Drawing SD-15168-001</td><td>fpc.html">Molex FFC – FPC connector<!--</td--></pre>

This document was generated on 03/09/2016

Be sure to match like plating

This document was generated on 03/09/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION