

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151680277

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



## K one company > a world of innovation

| This document was generated on 03/07/2016<br>PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION |   |  |  |
|---|---|--|--|
| Part Number:<br>Status:   | <u>0151680277</u>   |  |  |
|   | Active  |  |  |
| Overview:   | Premo-Flex <sup>™</sup> Cable Jur   |  |  |
| Description:  | 1.25mm Pitch Premo-Flex <sup>™</sup> FFC Jumper, Same Side Contacts (Type A), 22 Circuits, 0.03m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating |  |  |
| Documents:<br>Drawing (PDF)<br>Product Specification  | PS-15168-001 (PDF)  | Packaging Specification PK-15168-001 (PDF)<br>RoHS Certificate of Compliance (PDF) |  |
| General   |   |  | Series image - Reference only  |
| Product Family  |   | Cable  |  |
| Series  |   | 15168  | EUELV  |
| Comments  |   | Contacts on the same side, Type A  | Not Reviewed   |
| Crimp Quality Equipm  | ent   | Yes  |  |
| Overview  |   | Premo-Flex <sup>™</sup> Cable Jumpers  | EU RoHS China RoHS   |
| Product Name  |   | Premo-Flex™FFC Jumper  | Not Reviewed   |
| UPC   |   | 884982856875   | REACH SVHC   |
| 0.0   |   | 00100200000  | Not Reviewed   |
| Physical  |   |  | Halogen-Free   |
| Cable Length  |   | 0.031m   | Status   |
| Circuits (Loaded)   |   | 22   | Not Reviewed   |
| Circuits (maximum)  |   | 22   | Need more information on product   |
| Net Weight  |   | 1.000/g  | environmental compliance?  |
| Packaging Type  |   | Bag  | •  |
| Pitch - Termination Interface   |   | 1.25mm   | Email productcompliance@molex.com  |
| Temperature Range - Operating   |   | -40°C to +105°C  | Please visit the Contact Us section for any  |
| Wire Size AWG   |   | N/A  | non-product compliance questions.  |
| Wire/Cable Type   |   | Flat Flex Cable  | China ROHS Not Reviewed  |
| Electrical  |   |  | ELV Not Reviewed   |
| Current - Maximum pe  | er Contact  | 1.4A   |  |
| Voltage - Maximum   |   | 60V AC   |  |
| Material Info   |   |  | Search Parts in this Series<br><u>15168</u> Series   |
| Reference - Drawing   |   |  |  |
| Packaging Specification   | on  | PK-15168-001   | Use With   |
| Product Specification   |   | PS-15168-001   | <a href="www.molex.com/link/ffc-&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Sales Drawing&lt;/td&gt;&lt;td&gt;&lt;/td&gt;&lt;td&gt;SD-15168-001&lt;/td&gt;&lt;td&gt;fpc.html">Molex FFC – FPC connectorBe sure to match like plating</a> |

This document was generated on 03/07/2016

This document was generated on 03/07/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION