

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[KEMET](#)  
[CWR09JC226KB](#)


For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

**KEMET Part Number: T409H226K020BC**  
 (CWR09JC226KB)



Capacitor, Tantalum, 22 uF, 7238, +/-10% Tol, -55/+125C, 20 VDC (85C), Failure Rate=B (0.1%/1000 Hrs)



**Dimensions (mm)**

Symbol	Dimension	Tolerance
L	7.24	+/-0.38
W	3.81	+/-0.38
H	2.79	+/-0.38
K	1.52	MIN
F	3.68	+0.13/-0.51
S	1.27	+0.025/-0.13
P	0.76	MIN
A	4.7	NOM

**Notes:**

-Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K", "F" And "S"

-P And R Dimensions Represents The Minimum Solderable Area Of The Termination Surface Entirely Below Cutout (If One Is Present)

**General Information**

Supplier:	KEMET
Application:	MIL-PRF-55365/4
Part Type Description:	SMD, MnO <sub>2</sub> , Molded, Military Equivalent
Construction:	Standard Chip-MnO <sub>2</sub>
Body Type:	SMD Chip
Termination:	Hot Solder Dipped
Footprint:	7238
Weight:	349.01 mg
Approvals:	MIL-PRF-55365/4, CWR09 Style
RoHS:	No

**Specifications**

Capacitance:	22 uF
Tolerance:	+/-10%
Voltage:	20 VDC (85C)
Voltage:	13.4 VDC (125C)
Temperature Range:	-55/+125C
Testing:	Standard Testing Only
Resistance/ESR:	0.9 Ohms (100kHz)
Failure Rate:	B (0.1%/1000 Hrs)
Leakage Current:	4 uA
Dissipation Factor:	6%

**Packaging Specifications**

Package Kind:	T&R
Package Size:	7 in/180 mm
Package Quantity:	500