

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1663116](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



Extract from the online catalog

SACC-M12MS-5CON-PG 7-M

Order No.: 1663116



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663116>

Sensor/actuator connector, male, straight, 5-pos., M12, A-coded, screw connection, metal knurl, cable screw connection Pg7

Commercial data	
EAN	4017918116583
Pack	1 pcs.
Customs tariff	85366990
Weight/Piece	0.02313 KG
Catalog page information	Page 45 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
06/12/2006



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Nominal current I_N	4 A
Nominal voltage U_N	60 V
Number of positions	5
Volume resistance	$\leq 8 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$

SACC-M12MS-5CON-PG 7-M Order No.: 1663116
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663116>

Ambient temperature (operation)	-40 °C ... 85 °C (plug/socket)
General characteristics	
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuZn
Contact surface material	CuSnZn
Contact carrier material	PA 66
Material of grip body	PBT
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	NBR
Type of connection	Screw connection
Conductor cross section stranded min.	0.25 mm ²
Conductor cross section stranded max.	0.75 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	18
Min. diameter	4 mm
Max. diameter	6 mm
Status display	No

Certificates / Approvals



Certification CUL, GOST, UL

Accessories


Item	Designation	Description
General		
1436505	SACC-M12-SET/2,5-3,5	Sensor/actuator connector, accessories, pressure screw and Pg7 seal, for unshielded M12 connector, cable diameter 2.5 mm - 3.5 mm

SACC-M12MS-5CON-PG 7-M Order No.: 1663116

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663116>



Diagrams/Drawings

Dimensioned drawing



M12 x 1 male connector, straight


Schematic diagram



Male/Female M12

Cable connection side M12 (screw connection)

Pin assignment M12 male connector, 5-pos., A-coded, male side



SACC-M12MS-5CON-PG 7-M Order No.: 1663116

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663116>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;