

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2280077](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



Extract from the online catalog

FLK 10

Order No.: 2280077



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2280077>

VARIOFACE module, with screw connection and flat-ribbon cable plug connector, for mounting on NS 32 or NS 35/7.5, with male connector and short and long locking latches for female connectors, 10-pos. (separate test socket for each channel)

Commercial data	
EAN	4017918054328
Pack	10 pcs.
Customs tariff	85369010
Weight/Piece	0.09713 KG
Catalog page information	Page 242 (IF-2007)

Product notes

WEEE/RoHS-compliant since:
05/02/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Nominal voltage U_N	< 50 V AC
	60 V DC
Max. current carrying capacity per branch	1 A

FLK 10 Order No.: 2280077

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2280077>

Number of positions	10
Width	60 mm
Height	58.5 mm
Depth	50 mm
Status display	No
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Test voltage	800 V AC (50 Hz, 1 min.)
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Pollution degree	2
Surge voltage category	II

Connection data

Connection 1	PCB connection
Connection in acc. with standard	IEC / EN
Type of connection	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M3
Connection 2	Flat-ribbon cable connector in acc. with IEC 60603-13
Type of connection	Pluggable
Number of positions	10

Certificates / Approvals


Certification

GOST

FLK 10 Order No.: 2280077

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2280077>

Accessories

Item	Designation	Description
------	-------------	-------------

Cable/conductor

2299204	FLK 10/EZ-DR/ 50/KONFEK	Round cable set, with two 10-pos. socket strips, (1:1 connection), cable length: 0.5 m
2299217	FLK 10/EZ-DR/ 100/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 1 m
2299220	FLK 10/EZ-DR/ 150/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 1.5 m
2299233	FLK 10/EZ-DR/ 200/KONFEK	Round cable set, with two 10-pos. socket strips, (1:1 connection), cable length: 2 m
2299246	FLK 10/EZ-DR/ 300/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 3 m
2299259	FLK 10/EZ-DR/ 400/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 4 m
2299262	FLK 10/EZ-DR/ 600/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 6 m
2299275	FLK 10/EZ-DR/ 800/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 8 m
2299288	FLK 10/EZ-DR/1000/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 10 m
2295059	FLK EZ-DR.../.../...	Round cable, with preassembly, not shielded, variable cable length

Plug/Adapter

0201647	RPS	Reducing plug, Color: gray
---------	-----	----------------------------

FLK 10 Order No.: 2280077

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2280077>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;