

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2943796](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

CM 90-PS-120AC/ 2X12DC/1



► General data



Power supply unit, common-mode, input 120 V AC, output 2 x 12 V DC/1 A

Order number

2943796

Type

CM 90-PS-120AC/ 2X12DC/1

Barcode number

4017918081348

Unit pack

1 Pcs.

Customs tariff

85044094000

► Technical data

Input data

Nominal input voltage

120 V AC +6 % -10 %

Frequency range

50 Hz ... 60 Hz

Nominal power consumption

65 VA

Input fuse

Thermal release fuse

CM 90-PS-120AC/ 2X12DC/1

Output data

Nominal output voltage	$\pm 12 \text{ V DC } \pm 4 \%$
Output current	1 A (2 x)
Residual ripple	< 30 mVss
Output fuse	IEC 127-2/EN 60 127-2 (2 x)
Protective circuit/component	Damping diode, varistor

General data

Width	90 mm
Height	146 mm
Depth	75 mm
Weight	1.5 kg
Operating mode	100% operating factor
Test voltage input/output	4 kV AC
Degree of protection	IP 20
Ambient temperature (operation)	0 °C ... 60 °C
Installation position	On horizontal DIN rail, venting slits above and below
Assembly instructions	Can be aligned with spacing = 10 mm
Standards/regulations	IEC 664/IEC 664 A/DIN VDE 0110-1:1989-01
Standards/regulations	DIN VDE 0551

Connection data, input

Screw thread	M 2,5
Stripping length	8 mm
Type of connection	Screw connection
Min. conductor cross section AWG/kcmil	24
Conductor cross section AWG/kcmil max	14
Min. conductor cross section, rigid	0.2 mm ²
Conductor cross section, rigid max.	2.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Max. conductor cross section, flexible	2.5 mm ²

Connection data, output


Stripping length	8 mm
Type of connection	Screw connection
Min. conductor cross section AWG/kcmil	24
Conductor cross section AWG/kcmil max	14
Min. conductor cross section, rigid	0.2 mm ²
Conductor cross section, rigid max.	2.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Max. conductor cross section, flexible	2.5 mm ²

CM 90-PS-120AC/ 2X12DC/1




▸ Drawings

Diagram



Circuit diagram



CM 90-PS-120AC/ 2X12DC/1



► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved