

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Bel Fuse Inc.](#)
[ADBJ20-E3-BJ79](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

RED INDICATES ORIGINAL

DWG SIZE		C		REVISIONS			12-01	SH 1
				REV	CD	DESCRIPTION	DWN	APPROVED
				J	11191	ADDED C.701L, -201 THRU -220; ADDED ITEM 34; SEE ECD	DKC	

P2 CONN TYPE	FIG NO	P1 CONN TYPE																			
		BL20					UBL20					BL40					UBL40				
		E1	E2	E3	E4	E5	E1	E2	E3	E4	E5	E1	E2	E3	E4	E5	E1	E2	E3	E4	E5
DASH NUMBERS																					
B.774	1A	-1	-2	-3	-4	-169	-5	-6	-7	-8	-170	-9	-10	-11	-12	-171	-13	-14	-15	-16	-172
B.774TL	1A	-17	-18	-19	-20	-173	-21	-22	-23	-24	-174	-25	-26	-27	-28	-175	-29	-30	-31	-32	-176
B.774FL	1A	-33	-34	-35	-36	-177	-37	-38	-39	-40	-178	-41	-42	-43	-44	-179	-45	-46	-47	-48	-180
B.774	1B	-49	-50	-51	-52	-181	-53	-54	-55	-56	-182	-57	-58	-59	-60	-183	-61	-62	-63	-64	-184
B.779	2A	-65	-66	-67	-68	-185	-69	-70	-71	-72	-186	-73	-74	-75	-76	-187	-77	-78	-79	-80	-188
B.779TL	2A	-81	-82	-83	-84	-189	-85	-86	-87	-88	-190	-89	-90	-91	-92	-191	-93	-94	-95	-96	-192
B.779FL	2A	-97	-98	-99	-100	-193	-101	-102	-103	-104	-194	-105	-106	-107	-108	-195	-109	-110	-111	-112	-196
B.779	2B	-113	-114	-115	-116	-197	-117	-118	-119	-120	-198	-121	-122	-123	-124	-199	-125	-126	-127	-128	-200
C.770	3A	-129	-130	-131	-132	-133	-134	-135	-136	-137	-138	-139	-140	-141	-142	-143	-144	-145	-146	-147	-148
C.770	3B	-149	-150	-151	-152	-153	-154	-155	-156	-157	-158	-159	-160	-161	-162	-163	-164	-165	-166	-167	-168
C.770TL	3A	-201	-202	-203	-204	-205	-206	-207	-208	-209	-210	-211	-212	-213	-214	-215	-216	-217	-218	-219	-220

FIG 1A (P1)
-1 SHOWN
-57 SHOWN
FIG 1B (P1)

FIG 2A (P1)
-65 SHOWN
-121 SHOWN
FIG 2B (P1)

FIG 3A (P1)
-129 SHOWN
-159 SHOWN
FIG 3B (P2)

INCH	MM
.005	0.13
.030	0.76
.109	2.77
.140	3.56
.219	5.54
.221	5.61
.281	7.14
.284	7.21
.606	15.69
.510	12.95
.593	15.06
.625	15.88
.630	16.00
.635	16.13
.687	17.45
.750	19.05
.800	20.32
1.835	46.61

RECOMMENDED
PANEL CUTOUT
FOR -1 THRU -64
MAX. PNL THK .140

RECOMMENDED
PANEL CUTOUT
FOR -65 THRU -128
MAX. PNL THK .109

FOR OPTIONAL GROUND TERMINAL ADD PREFIX "G" TO DASH NO (-G1 ETC)

3. BETWEEN SERIES ADAPTER, 50 & 75 OHM BNC/TNC COAXIAL JACK TO CONCENTRIC TWINAX/TRIAX INSULATED & NONINSULATED BULKHEAD MOUNT JACK

2. FINISH: TFS-1A (NICKEL)

1. ALL DIM ARE IN INCHES

QTY	DESCRIPTION	PART NUMBER	ITEM
TOL UNLESS SPECIFIED XXX ± .005 XXX ± .005 XXX ± .005 XXX ± .005	TROMPETER RF connectivity	ADAPTERS: U/B.20/40 TO "70" SERIES BULKHEAD MOUNT	
DWN	DKC	8-1-95	MATERIAL CODE IDENT
ENGR			14949
APPR			DRAWING NO.
			12-01
			REV
			J
			SCALE 2/1
			DATE 8/17/85
			SHEET 1 OF 2