

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 1301350292

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 1301350292 - ANGL PWR DIST BX 125V20A 50FT Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

one company > a world of innovation

Pert Number: 1301350292 Status: Outlet Boxes Description: Sublet Boxes Bescription: Sublet Boxes Bescription: Sublet Boxes RoltS Certificate of Compliance (PDF) Product Literature (PDF) Series insige: 130135 RoltS Certificate of Compliance (PDF) Product Literature (PDF) Series insige: 130135 Enclosure Rating N/A GFOR Reset: N/A Open Neutral Relay N/A Open Neutral Relay N/A Open Neutral Relay N/A Open Neutral Relay N/A Not Reviewed Buple Soft 737 Product Instrute Order No Super-Safeway?* Not Reviewed Duples Receptacle Type Duples Vype Angled Outlet Boxs UPC Techerone on product Woodnead Yes Product Instrute Order No Buples UPC Cord Type Duples Cord Length Safeway?* Not Reviewed Betael Hower Information on product Cord Type Soft Size	This document was generated on 07/05/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION					
Product Product Boxes Description: Super-Safeway® Angled Outlet Box, F3 (3/4') Cord Grip Body, Including (2) NEMA 5-20 Duplex Receptades & Plug, 15.24m (50.0) Cord Length, 12/3 SOW Cord Decuments: RoHS Centificate of Compliance (PDF) Product Family Product Family Product Family Series 130135 Enclosure Rating Mounting Style Overview Outlet Boxes Product Tamily Protable Oper Neutral Relay N/A Mounting Style Product Literature Order No 987650-7737 Product Literature Order No 9876520-7737 Product Literature Order No 9876520-7737 Product Literature Order No 9876520-7737 Vice Voc 700-0000000000000000000000000000000000	Part Number:	1301350292				
Overview: Outline Boxes Super-Safeway® Angled Outlet Box, F3 (3/4') Cord Grip Body, Including (2) NEMA 5-20 Duplex Receptacles & Plug, 15.24m (50.0') Cord Length, 12/3 SOW Cord Documents: RoHS Certificate of Compliance (PDF) Product Literature (PDF) General Product Family Product Family Power Distribution Series 130135 Enclosure Rating N/A Open Neutral Relay N/A Open Neutral Relay N/A Oren Neutral Relay Outlet Boxes Product Literature Order No 987650-7737 Product Literature Order No 98768228890 Woodhead Yes Physical Enclose Carton Cord Gip Body Size F3 34/* Cord Opidy Size Carton Electrical Not Reviewed Cord Type Carton Electrical Not Reviewed <th>Status:</th> <th>Active</th> <th></th> <th></th> <th></th>	Status:	Active				
Description: Super-Safeway® Angled Outlet Box, F3 (34*) Cord Grip Body, Including (2) NEMA 5-20 Duplex Receptacles & Plug, 15.24m (50.0°) Cord Length, 12/3 SOW Cord Documents: RothS Centificate of Compliance (PDF) Product Literature (PDF) General Product Family Power Distribution Series 130135 Encource Rating NA GFC I Reset N/A China RoHS China RoHS Overview Outlet Boxes Product Literature (PDF) EU EUV Not Reviewed Product Literature Order No 987650-7737 Product Literature Order No 987650-7737 Product Literature Order No 987650-7737 Product Literature (BOP) EU EUV Not Reviewed UPC 79678828890 Woothead Yes Not Reviewed Not Reviewed Physical Cord Diameter 15.24m (60°) Email (60°) Email productompliance @molex.com Email productompliance @molex.com Pip Lid No Reviewed Not Reviewed ELV Not Reviewed Number of Receptacles 2 Packaging Type Card Grip Bod Size China RoHS Not Reviewed Reach Thru No Rubber No Not Re	Overview:					
5-20 Duplex Receptacles & Plug, 15.24m (50.0°) Cord Length, 12/3 SOW Cord Documents: RoHS Certificate of Compliance (PDF) Product Literature (PDF) General Series Image - Reference only Product Family Power Distribution Series Series Image - Reference only General NA Product Iterature Order No Series Image - Reference only Wood Reset NA Mounting Style Portable Open Neutral Relay NA Overview Outlet Boxses Product Literature Order No Series Jange - Reference only Wood Reset Product Literature Order No Product Pame Duplex Type Duplex Ord Col Literature Order No Series Jange - Reference only Wood Reset Product Literature Order No Physical Cord Diameter 15.24m (60.0°) Cord Length No Pipsical Cord Compliance Questions. China ROHS <td></td> <td></td> <td>et Box_E3 (3/4") Cord Grip Body_Including (2) NEMA</td> <td></td> <td>11 min 1</td>			et Box_E3 (3/4") Cord Grip Body_Including (2) NEMA		11 min 1	
Documents: RoHS Certificate of Compliance (PDF) Product Literature (PDF) Series 130135 Product Family Power Distribution Series 130135 Enclosure Rating N/A GFC1 Reset N/A Mounting Style Portable Overview Quilet Boxes Product Literature Order No 987650-7737 Product Difference Duplex Type Angled Outlet Box UPC 7867822890 Woodhead Yes Physical Cord Diameter Cord Diameter 15.24mm (500°) Cord Grip Body Size F3 344' Cord Jength 15.24mm (500°) Fipi Lid No Material - Housing Rubber Number of Receptacies 2 Packaging Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Not Reviewed 130135 Series	Decemption				and see	
RoHS Certificate of Compliance (PDE) Product Literature (PDE) General Series Product Family Power Distribution Series 130135 Enclosure Rating N/A GFCI Reset N/A Overview Outlet Boxes Product Literature Order No 987650-7737 Product Iserature Order No 987650-7737 Product Name Super-Safeway TM Receptacle Type Duplex Type Angled Outlet Box UPC 7867882890 Woodhead Yes Physical Teal (500°) Cord Grip Body Size F3 3/4" Cord Grip Body Size F3 3/4" Cord Grip Body Size 2 Packaging Type Carton Electrical No Current - Maximum per Contact 20.0A GFCI No Group Straine 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Steries Series in this Series 12015 No Steries No						
RoHS Certificate of Compliance (PDE) Product Literature (PDE) General Series Product Family Power Distribution Series 130135 Enclosure Rating N/A GFCI Reset N/A Overview Outlet Boxes Product Literature Order No 987650-7737 Product Iserature Order No 987650-7737 Product Name Super-Safeway TM Receptacle Type Duplex Type Angled Outlet Box UPC 7867882890 Woodhead Yes Physical Teal (500°) Cord Grip Body Size F3 3/4" Cord Grip Body Size F3 3/4" Cord Grip Body Size 2 Packaging Type Carton Electrical No Current - Maximum per Contact 20.0A GFCI No Group Straine 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Steries Series in this Series 12015 No Steries No	Documents:					
Product Family Power Distribution Series image - Reference only Series 130135 Enclosure Rating N/A GFCI Reset N/A Mounting Style Portable Open Neutral Relay N/A Overview Outlet Boxes Product Literature Order No 987650-7737 Product Literature Order No 987650-7737 Product Name Super-Safeway TM Receptacle Type Angled Outlet Box UPC 78678828690 Woodhead Yes Physical Cord Diameter Cord Diameter 15.24mm (.600") Cord Diameter 15.24m (.600") Cord Diameter 15.24m (.600") Cord Grip Body Size F3 3/4" Cord Truu No Number of Receptacles 2 Packaging Type Carton Electrical Carton Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V <td></td> <td>mpliance (PDF)</td> <td>Product Literature (PDF)</td> <td></td> <td></td>		mpliance (PDF)	Product Literature (PDF)			
Product Family Power Distribution Series image - Reference only Series 130135 Enclosure Rating N/A GFCI Reset N/A Mounting Style Portable Open Neutral Relay N/A Overview Outlet Boxes Product Literature Order No 987650-7737 Product Literature Order No 987650-7737 Product Name Super-Safeway TM Receptacle Type Angled Outlet Box UPC 78678828690 Woodhead Yes Physical Cord Diameter Cord Diameter 15.24mm (.600") Cord Diameter 15.24m (.600") Cord Diameter 15.24m (.600") Cord Grip Body Size F3 3/4" Cord Truu No Number of Receptacles 2 Packaging Type Carton Electrical Carton Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V <td></td> <td>• • •</td> <td></td> <td></td> <td></td>		• • •				
Product Family Power Distribution Series image - Reference only Series 130135 Enclosure Rating N/A GFCI Reset N/A Mounting Style Portable Open Neutral Relay N/A Overview Outlet Boxes Product Literature Order No 987650-7737 Product Literature Order No 987650-7737 Product Name Super-Safeway TM Receptacle Type Angled Outlet Box UPC 78678828690 Woodhead Yes Physical Cord Diameter Cord Diameter 15.24mm (.600") Cord Diameter 15.24m (.600") Cord Diameter 15.24m (.600") Cord Grip Body Size F3 3/4" Cord Truu No Number of Receptacles 2 Packaging Type Carton Electrical Carton Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V <td>General</td> <td></td> <td></td> <td></td> <td></td>	General					
Enclosure RatingN/AEU ELVGFCI ResetN/ANot ReviewedMounting StylePortableOpen Neutral RelayN/ANot ReviewedOverviewQutlet BoxesNot ReviewedProduct Literature Order No987650-7737REACH SVHCProduct Literature Order No987650-7737Not ReviewedReceptacle TypeDuplexHalogen-FreeUPC78678828890Not ReviewedWootheadYesStatusPhysicalCord Grip Body SizeF3 3/4*Cord Diameter15.24mm (.600*)Email product compliance @ molex.comCord Grip Body SizeF3 3/4*Please visit the Contact Us section for any non-product compliance questions.Field LidNoNoMaterial - HousingRubberNumber of Receptacles2Packaging Type12/3 SOWCurrent - Maximum per Contact20.0AGFCINoCord DingurationNEMA 5-20Voltage - Maximum125V			Power Distribution	Series imag	e - Reference only	
GFCI Reset N/A Not Reviewed Mounting Style Portable Portable Open Neutral Relay N/A Not Reviewed Product Literature Order No 987650-7737 Not Reviewed Product Name Super-Safeway™ Not Reviewed Receptacle Type Duplex Halogen-Free Type Angled Outlet Boxs Not Reviewed Woodhead Yes Not Reviewed Physical Cord Diameter 15.24mm (.600") Cord Length 15.24m (50.0') Please visit the <u>Contact Us</u> section for any non-product compliance questions. Flip Lid Not Reviewed ELV Not Reviewed Mumber of Receptacles 2 Packaging Type Cord Type 12/3 SOW China RoHS Current - Maximum per Contact 20.0A Series Groud Continuity Monitor No Not Reviewed NeEMA Configuration NeEMA 5-20 Voltage - Maximum			<u>130135</u>			
Mounting StylePortableEU RoHSChina RoHSOpen Neutral RelayN/ANot ReviewedOverviewQutlet BoxesNot ReviewedProduct Literature Order No987650-7737REACH SVHCProduct NameSuper-Safeway™Not ReviewedReceptacle TypeDuplexHalogen-FreeTypeAngled Outlet BoxStatusUPC7867828890Not ReviewedWoodheadYesNot ReviewedPhysicalCord Diameter15.24mm (.600")Cord Diameter15.24mm (.600")Email product compliance@molex.comCord Grip Body SizeF3 3/4"Please visit the Contact Us section for any non-product compliance questions.Fibe LidNoChina ROHSMumber of Receptacles2CurrentNumber of Receptacles22Packaging Type12/3 SOWSearch Parts in this SeriesCurrent - Maximum per Contact20.0ASeriesGFCINoNoNEMA ConfigurationNEMA 5-20Voltage - Maximum125V			N/A	EU ELV		
Open Neutral RelayN/AEU RoHSChina RoHSOverviewOutlet BoxesNot ReviewedNot ReviewedProduct Literature Order No987650-7737REACH SVHCProduct NameSuper-Safeway™Not ReviewedReceptacle TypeDuplexHalogen-FreeTypeAngled Outlet BoxStatusUPC78678828890Not ReviewedWoodheadYesNot ReviewedPhysicalEmail productompliance @molex.comCord Diameter15.24m (.600")Email productcompliance @molex.comCord Length15.24m (50.0')Email product compliance questions.Flip LidNoNot ReviewedNumber of Receptacles2CartonElectricalCartonELVCord Type12/3 SOWCurrent - Maximum per Contact20.0AGFCINoNEMA ConfigurationNEMA 5-20Voltage - Maximum125V				Not Reviewed		
OverviewOutlet BoxesNot ReviewedProduct Literature Order No987650-7737REACH SVHCProduct NameSuper-Safeway™Not ReviewedReceptacle TypeDuplexHalogen-FreeTypeAngled Outlet BoxStatusUPC78678828890Not ReviewedWoodheadYesNot ReviewedPhysicalEmail product compliance?Cord Diameter15.24mm (.600")Email product compliance?Cord Grip Body SizeF3 3/4"Please visit the Contact Us section for any non-product compliance questions.Cord Grip Body Size2Chrina ROHSCord Grip Body Size2Chrina ROHSCord Sign TypeCartonChina ROHSElectricalCortonCord Type12/3 SOWCurrent - Maximum per Contact20.0AGFCINoNeMA ConfigurationNEMA 5-20Voltage - Maximum125V			Portable			
Owner of the systemDates of the systemProduct Literature Order No987650-7737Product NameSuper-Safeway™Receptacle TypeDuplexTypeAngled Outlet BoxUPC78678828890WoodheadYesPhysical					China RoHS	
Induct Literative Order Not Stronger Safeway™ Product Name Super-Safeway™ Receptacle Type Duplex Type Angled Outlet Box UPC 78678828890 Woodhead Yes Physical Not Reviewed Cord Diameter 15.24mm (.600") Cord Grip Body Size F3 3/4" Cord Length 15.24m (50.0") Feed-Thru No Flip Lid No Number of Receptacles 2 Packaging Type Carton Electrical Cord Type Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Ground Continuity Monitor No No NeEMA 5-20 Voltage - Maximum 125V						
House Halle Super Saleway Receptacle Type Duplex Type Angled Outlet Box UPC 78678828890 Woodhead Yes Physical Email productompliance@molex.com Cord Diameter 15.24mm (.600") Cord Grip Body Size F3 3/4" Cord Length 15.24m (50.0") Feed-Thru No Flip Lid No Mumber of Receptacles 2 Packaging Type Carton Electrical Cord Type Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Ground Continuity Monitor No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V		er No				
TypeAngled Outlet BoxTypeAngled Outlet BoxUPC78678828890WoodheadYesPhysicalEmail product compliance?Cord Diameter15.24mm (.600")Cord Grip Body SizeF3 3/4"Cord Length15.24m (50.0")Feed-ThruNoFilp LidNoMaterial - HousingRubberNumber of Receptacles2Packaging TypeCartonElectricalSearch Parts in this SeriesCord Type12/3 SOWCurrent - Maximum per Contact20.0AGFCINoGround Continuity MonitorNoNEMA ConfigurationNEMA 5-20Voltage - Maximum125V						
Not ReviewedUPC7867828890WoodheadYesPhysicalNot ReviewedCord Diameter15.24mm (.600")Cord Grip Body SizeF3 3/4"Cord Length15.24m (50.0')Feed-ThruNoFlip LidNoMaterial - HousingRubberNumber of Receptacles2Packaging TypeCartonElectricalSearch Parts in this SeriesCord Type12/3 SOWCurrent - Maximum per Contact20.0AGround Continuity MonitorNoNet MA configurationNEMA 5-20Voltage - Maximum125V						
Or C Physical Cord Diameter 15.24mm (.600") Cord Diameter 15.24mm (.600") Cord Grip Body Size F3 3/4" Cord Length 15.24m (50.0") Feed-Thru No Filp Lid No Material - Housing Rubber Number of Receptacles 2 Packaging Type Carton Electrical Search Parts in this Series Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No NeMA Configuration NEMA 5-20 Voltage - Maximum 125V						
Physical environmental compliance? Cord Diameter 15.24mm (.600") Cord Cing Body Size F3 3/4" Cord Length 15.24m (50.0') Feed-Thru No Flip Lid No Material - Housing Rubber Number of Receptacles 2 Packaging Type Carton Electrical Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Ground Continuity Monitor No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V					ation on product	
PhysicalEmail product compliance @molex.comCord Diameter15.24mm (.600")Email product compliance @molex.comCord Grip Body SizeF3 3/4"Please visit the Contact Us section for any non-product compliance questions.Cord Length15.24m (50.0')China ROHSFeed-ThruNoChina ROHSNot ReviewedFlip LidNoChina ROHSNot ReviewedMaterial - HousingRubberNot ReviewedELVNumber of Receptacles22Search Parts in this SeriesPackaging TypeCartonSearch Parts in this SeriesElectrical20.0AGFCINoGround Continuity MonitorNoNoNEMA ConfigurationNEMA 5-20Voltage - MaximumVoltage - Maximum125VSearch Parts in this Series	woodnead		res			
Cord Grip Body SizeF3 3/4"Please visit the Contact Us section for any non-product compliance questions.Cord Length15.24m (50.0')Please visit the Contact Us section for any non-product compliance questions.Filip LidNoChina ROHSNot ReviewedMaterial - HousingRubberNot ReviewedELVNumber of Receptacles2Packaging TypeCartonElectricalSearch Parts in this Series130135 SeriesCord Type12/3 SOW1200AIsonaCurrent - Maximum per Contact20.0ASeriesGFCINoNoNEMA 5-20Voltage - Maximum125VNemax	Physical				inpliance :	
Cord Length15.24m (50.0')non-product compliance questions.Feed-ThruNoFlip LidNoMaterial - HousingRubberNumber of Receptacles2Packaging TypeCartonElectricalCord TypeCord Type12/3 SOWCurrent - Maximum per Contact20.0AGFCINoGround Continuity MonitorNoNEMA ConfigurationNEMA 5-20Voltage - Maximum125V	Cord Diameter		15.24mm (.600")			
Feed-ThruNoChina ROHSNot ReviewedFlip LidNoChina ROHSNot ReviewedMaterial - HousingRubberELVNot ReviewedNumber of Receptacles2Packaging TypeCartonElectricalCord Type12/3 SOW130135 SeriesCurrent - Maximum per Contact20.0AGFCINoGround Continuity MonitorNoNetMA 5-20Voltage - Maximum125V125VNot Reviewed			F3 3/4"			
Flip Lid No China ROHS Not Reviewed Material - Housing Rubber Not Reviewed ELV Not Reviewed Number of Receptacles 2 Packaging Type Carton Electrical Electrical 20.0A GFCI No Search Parts in this Series GFCI No Ground Continuity Monitor No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V			15.24m (50.0')	non-product complia	ance questions.	
Hip Lid No Material - Housing Rubber Number of Receptacles 2 Packaging Type Carton Electrical Search Parts in this Series Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Ground Continuity Monitor No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V				China POHS	Not Poviewod	
Material - Housing Rubber Number of Receptacles 2 Packaging Type Carton Electrical Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Ground Continuity Monitor No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V						
Packaging Type Carton Electrical Search Parts in this Series Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Ground Continuity Monitor No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V						
Electrical Search Parts in this Series Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Ground Continuity Monitor No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V		6	—			
Electrical 12/3 SOW Cord Type 12/3 SOW Current - Maximum per Contact 20.0A GFCI No Ground Continuity Monitor No NEMA Configuration NEMA 5-20 Voltage - Maximum 125V	Packaging Type		Carton			
Cord Type12/3 SOWCurrent - Maximum per Contact20.0AGFCINoGround Continuity MonitorNoNEMA ConfigurationNEMA 5-20Voltage - Maximum125V	Electrical				inis Series	
Current - Maximum per Contact20.0AGFCINoGround Continuity MonitorNoNEMA ConfigurationNEMA 5-20Voltage - Maximum125V			12/3 SOW	130135 Series		
GFCINoGround Continuity MonitorNoNEMA ConfigurationNEMA 5-20Voltage - Maximum125V		Contact				
NEMA ConfigurationNEMA 5-20Voltage - Maximum125V						
Voltage - Maximum 125V		litor	No			
			NEMA 5-20			
	Voltage - Maximum		125V			
Material Info	Material Info					
Old Part Number 3332B123			3332B123			

This document was generated on 07/05/2016

This document was generated on 07/05/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION