

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[3240152](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Connector - C-SCF 1/2,8X0,5 - 3240152

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Slip-on sleeve, non-insulated, 0.5 - 1 mm², 2.8 x 0.5

Product Features

- ✓ They round out the product range in terms of connectors
- ✓ The uninsulated slip-on sleeves and flat plugs are made from electrolytically tin-plated brass
- ✓



Key commercial data

Packing unit	1 pc
Minimum order quantity	100 pc
Weight per Piece (excluding packing)	0.2 GRM
Custom tariff number	85369010
Country of origin	Belgium

Technical data

Dimensions

Length (b)	14.5 mm
Width (a)	2.8 mm
Material thickness (g)	0.3 mm

Ambient conditions

Ambient temperature (operation)	110 °C
---------------------------------	--------

General

Color	silver
Stripping length	7 mm
Components	Halogen-free

Connector - C-SCF 1/2,8X0,5 - 3240152

Technical data

General

Material	Brass
----------	-------

Classifications

eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201

ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC001052
ETIM 5.0	EC001052

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Connector - C-SCF 1/2,8X0,5 - 3240152

Approvals

Approval details

EAC

Drawings

Dimensional drawing

