



Distributor of ITT Cannon, LLC: Excellent Integrated System Limited

Datasheet of MS3108R24-11SW - CONN PLUG 9POS RT ANG W/SKTS

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ITT Cannon, LLC](#)
[MS3108R24-11SW](#)


For any questions, you can email us directly:

sales@integrated-circuit.com



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 43.8 |
| B | 1 1/2-18NEF-2B |
| C | 1 7/16-18NEF-2A |
| D | 43.3 |
| E | 27.6 |
| F | 32.5 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3 | DICHTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 10 | DICHTRING FRONT / FRONT SEALING RING |
| 12 | ENDGEHÄUSE / ENDBELL |



| |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential. |
| Specification and Dimensions subject to change Drawings illustrate normal insulator positioning |
| Material Specification: |
| Shell Material: Aluminium alloy |
| Shell Plating: Olive drab chromate coating over cadmium plating |
| Insulator Material: Neoprene |
| Contact Material: Copper alloy |
| Contact Plating: Hard silver |

| | |
|---|--|
| all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m | drawing for CUSTOMER |
| ITT Engineered for life ITT CANNON GERMANY D-71536 Weinstadt-Germersheim | description MS3108R24-11SW Plug 90° Shortened light-weight endbell without cable clamp Solder Cup / Socket / Layout: 24-11 |
| © All rights reserved. Reproduction or reuse in any form without prior written authorization of ITT Cannon | page 1/1 revision 377.3, Jul 16 |