

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Weidmüller](#)  
[1755270000](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

## Datasheet

### DEK 5/3,5 MC NEUTRAL

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-2083

www.weidmueller.com

The **dekafix (DEK)** marker is the universal marker for all conductor and plug-in connectors as well as for electronics modules. The system is ideal for small groups of consecutive numbers and covers a large range of ready-printed markers. Being mounted as strips means that they are quickly clipped on in one operation. The printing is legible with good contrast, and is available in five widths.

- large selection of ready-to-use markers,
- in strips for fast installation
- connector markers suitable for all Weidmüller conductor connectors,
- available as blank cards, MultiCard or as cards with standard printing.

#### General ordering data

|                  |   |
|------------------|---|
| Order No.        | <a href="#">1755270000</a>                    |
| Part designation | DEK 5/3,5 MC NEUTRAL                          |
| Version          | Connector markers, x 3.5 mm, Polyamide, white |
| GTIN (EAN)       | 4032248017348                                 |
| Qty.             | 500 pc(s).                                    |

**Datasheet**

**DEK 5/3,5 MC NEUTRAL**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com

**Technical data**

**Dimensions (1)**

|        |      |       |        |
|--------|------|-------|--------|
| Length | 5 mm | Width | 3.5 mm |
|--------|------|-------|--------|

**Markings**

|                                   |         |  |           |
|-----------------------------------|---------|--|-----------|
| Cadmium                           | No      | Can be labelled with thermal transfer printers | No        |
| Can be printed with plotter       | Yes     | Can be written with dot-matrix printer         | No        |
| Can be written with laser printer | No      | Flammability class UL 94                       | V-2       |
| Halogen                           | No      | Material                                       | Polyamide |
| Material colour                   | white   | Material colour according to resistance code 9 |           |
| Operating temperature range, max. | 100 °C  | Operating temperature range, min.              | -40 °C    |
| Pin can be written (STI)          | Yes     | Pitch in mm                                    | 3.5 mm    |
| Printed characters                | without | Silicone                                       | No        |
| Speed marking laser               | Yes     |  |           |

**Approvals**

|                      |          |
|----------------------|----------|
| Approvals institutes | GOSTME25 |
|----------------------|----------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| eClass 5.1 | 27-14-11-37 | eClass 6.0 | 27-14-11-37 |
|------------|-------------|------------|-------------|

**Downloads**

|      |   |
|------|---|
| STEP | <a href="#">1755270000_27470_DEK_5-3.5_MC_STP.stp</a> |
|------|---|