

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Greenlee Communications](#)  
[471/6](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



WIRE FERL INSUL

Insulated Wire Ferrules



Image  
Unavailable

Cat No: 471/6

UPC No: 783310045557

#### Description

---

- Terminate stranded wire into terminal blocks
- Electrolytic copper and tin plating provide maximum conductivity and low contact resistance

#### Specifications

---

- Color : Red
- Color Code : DIN 46228, Part 4
- Dimension Inches L2 : 0.236 IN (6.000 MM)
- Finish : Tin Plated
- Insulation : Polypropylene Plastic
- Material : Electrolytic Copper
- Recommended Crimping Tools : K1GL, K32GL, K36GL, K30GL, Die 03283
- Size : 0.471 IN (12.000 MM) Overall Length, 0.236 IN (6.000 MM) Sleeve Length
- Standard : CSA, LR 702418, NRTL/C, RoHS
- Type : Insulated
- Wire Size : 18-17 AWG (1.000 SQ-MM)
- Wire Type : Stranded